

4300V Series

Tubeaxial

119x119x32mm VARIOFAN



■ DC fans with electronically commutated external rotor motor. Fully integrated commutation electronics.

■ With electronic protection against reverse polarity, blocking and overloading by PTC-resistor partially impedance protected.

■ Temperature sensor (LZ370) must be ordered separately.

■ Mounting from either face using four 4.3 mm holes.

■ Fan of fiberglass reinforced plastic. PBTP housing, PA impeller.

■ Air exhaust over struts. Rotational direction CW looking at rotor.

■ Electrical connection via 3 leads AWG 22, TR 64. Stripped and tinned ends.

■ UL, CSA, VDE approvals on some models, please contact application engineering.

Part Number	CFM @ 0	Volts	Voltage Range	Power (W)	dBA	Max Ambient Temp C	Wgt. (lbs)	Type Of Bearing	Features
4312MV	40-82	12	8 to 13	1.5-3.0	22-39	65	0.5	Ball	Leads
4312V	50-100	12	8 to 13	2.4-5.5	29-45	65	0.5	Ball	Leads
4314V	50-100	24	21 to 27	3.0-5.4	29-45	65	0.5	Ball	Leads
4318V	40-100	48	40 to 53	2.6-5.4	21-45	65	0.5	Ball	Leads

