



Automatic Stripping Tool



Interchangeable stripping blade cassettes



Cuts & strips up to 10mm²/8 AWG - Strips PVC, THHW, TEFLON insulations



Ergonomic design with non-slip two component handles



Easy/snag free wire removal from tool - jaws stay open after strip



Self Adjusting Cut & Strip Tool



Straight Blade Cassette Stripping Range 0.02 - 10.0mm²



Cables: Conduit wire, Flex mains cable, Equipment wire, Flat modplug cable etc.

34-8 AWG

442 12 Self Adjusting Cutting & Stripping Tool

Easily interchangeable stripping cassettes enables a wide range of insulations from PVC to PTFE. Light weight soft grip handle qualified for high volume production and portable/field usage.

#442 12	mm	Inch	AWG	Strip Dim.	lbs.	Pkg.
	191	7.5	34 - 8	0.02-10mm²	.30	1



Replaceable Cassette - Straight Blade



Straight Blade Cassette Stripping Range 0.02 - 10.0mm²



34-8 AWG

Straight


442 14 Straight Blade Cassette, PVC Insulations

Fine adjustability ensures that thin insulations can be stripped without damage to conductors. At the end of the stripping function, the stripping blades open and remain open during the return phase of the strip cycle facilitating easy/snag free wire removal from the tool.

#442 14	mm	Inch	AWG	Strip Range	lbs.	Pkg.
			34 - 8	0.02-10mm²	.02	1



Replaceable Cassette - 4-16mm²



Stripping Range 4-16mm²



10-5 AWG

Radius Blade

442 69 Replaceable Cassette, 4-16mm Stripping Range

Fine adjustability ensures that thin insulations can be stripped without damage to conductors. At the end of the stripping function, the stripping blades open and remain open during the return phase of the strip cycle facilitating easy/snag free wire removal from the tool.

#442 69	mm	Inch	AWG	Strip Range	lbs.	Pkg.
			10 - 5	4-16mm²	.02	1



Replaceable Cassette - "V" Blade



"V" Blade Stripping Range 0.1 - 4mm²



28-12 AWG

VBC or PTFE

442 13 Replaceable VBC or PTFE Cassette, "V" Blade

Fine adjustability ensures that thin insulations can be stripped without damage to conductors. At the end of the stripping function, the stripping blades open and remain open during the return phase of the strip cycle facilitating easy/snag free wire removal from the tool.

#442 13	mm	Inch	AWG	Strip Range	lbs.	Pkg.
			28 - 12	0.1-4mm²	.02	1