

PART NO.	ENG. NO.	CIRCUIT SIZE	MATERIAL (SEE NOTE 1)	DIM. "A"	DIM. "B"	DIM. "C"
050-84-1010	42021-1A	1	A	1,080 (27.43)	.290 (7.37)	----
050-84-1011	42021-1B	1	B			
050-84-1015	42021-1C	1	C			
366430001	36643-001	1	D			
050-84-1020	42021-2A	2	A	1,080 (27.43)	.580 (14.73)	.300 (7.62)
050-84-1021	42021-2B	2	B			
050-84-1025	42021-2C	2	C			
366430002	36643-002	2	D			
050-84-1030	42021-3A	3	A	1,080 (27.43)	.580 (14.73)	.300 (7.62)
050-84-1031	42021-3B	3	B			
050-84-1035	42021-3C	3	C			
366430003	36643-003	3	D			
050-84-1040	42021-4A	4	A	1,080 (27.43)	.580 (14.73)	.300 (7.62)
050-84-1041	42021-4B	4	B			
050-84-1045	42021-4C	4	C			
366430004	36643-004	4	D			
050-84-1060	42021-6A	6	A	1,080 (27.43)	1,080 (27.43)	.800 (20.32)
050-84-1061	42021-6B	6	B			
050-84-1065	42021-6C	6	C			
366430005	36643-005	6	D			
PRELIMINARY	42021-8A	8	A	1,080 (27.43)	.580 (14.73)	.300 (7.62)
PRELIMINARY	42021-8B	8	B			
PRELIMINARY	42021-8C	8	C			
050-84-1090	42021-9A	9	A	1,080 (27.43)	1,080 (27.43)	.800 (20.32)
050-84-1091	42021-9B	9	B			
050-84-1095	42021-9C	9	C			
366430006	36643-006	9	D			
050-84-1120	42021-12A	12	A	1,080 (27.43)	1,080 (27.43)	.800 (20.32)
050-84-1121	42021-12B	12	B			
050-84-1125	42021-12C	12	C			
366430007	36643-007	12	D			
050-84-1150	42021-15A	15	A	1,080 (27.43)	1,080 (27.43)	.800 (20.32)
050-84-1151	42021-15B	15	B			
050-84-1155	42021-15C	15	C			
366430008	36643-008	15	D			

NOTES:

1) MATERIAL CODES:

"A"= NYLON TYPE 6/6, 94V-2
COLOR: NATURAL (WHITE/TRANSLUCENT)

"B"= NYLON TYPE 6/6, 94V-0
COLOR: (BRICK RED)

"C"= NYLON TYPE 6/6, 94V-0
COLOR: NATURAL (WHITE)

D= NYLON 94V-2
COLOUR:NATURAL,899921279
GLOW WIRE COMPATIBLE WITH CTI OF 325 VOLTS,
ACCORDING TO IEC 60335-4TH EDITION

2) UNLESS OTHERWISE INDICATED, DIMENSIONS
ARE FOR REFERENCE ONLY.

3) PLUG HOUSINGS MATE WITH :

- CAP HOUSINGS, .084/(2.13) DIA. SERIES: (42022-**)
- HEADER ASSEMBLY HOUSINGS,
.084/(2.13) DIA. SERIES: (A-42002-*****)

4) HOUSINGS DESIGNED TO BE USED WITH TERMINALS :


- PINS, .084/(2.13) DIA. SERIES: (42023-****)
- SOCKETS, .084/(2.13) DIA. SERIES: (42024-****)

5) CONTACTS ARE ON .250/(6.35) GRID CENTERLINE
SPACING.

6) PRODUCT SPECIFICATION PS-42022-0001 APPLIES.

7) LEGEND SCHEME IS NOT APPLICABLE FOR GLOW WIRE
COMPATIBLE PART NUMBERS

LEGEND:



ENTER DESCRIPTION EC NO: 12008-0611 2008/05/14 DRWNSJ CHKD:KPRASAD 2008/05/16 APPR:KPRASAD 2008/06/02	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± .010 2 PLACES ± 0.25 ± 0.14 1 PLACE ± 0.36 ± --- ANGULAR ± ---° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION STYLE IN/MM		SCALE 1.5:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	
				DRAWN BY RK	DATE 87/11/16	TITLE HOUSING, PLUG .084/(2.13) DIA. SERIES			
				CHECKED BY GWF	DATE 87/11/16	MOLEX INCORPORATED			
				APPROVED BY GWF	DATE 87/11/16	MATERIAL NO.			
				SEE TABLE		DOCUMENT NO.		SHEET NO.	
C1	REV			SIZE A2	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				