

Technical drawing of a mechanical part, showing two views: a top view (Fig. 1) and a side view (Fig. 2).

Fig. 1 (Top View): Shows a circular feature with a diameter of $\varnothing 1.6$. A central hole has a diameter of $\varnothing 0.57$. The drawing includes coordinate axes X, Y, and Z.

Fig. 2 (Side View): Shows the profile of the part with the following dimensions:

- Overall length: 2.8 ± 0.3
- Distance from the left end to the start of the first step: 1.5
- Distance between the first and second steps: 0.7
- Distance between the second and third steps: (0.8)
- Distance between the third and fourth steps: 0.5
- Distance from the left end to the start of the first step: 0.45
- Distance from the right end to the start of the last step: 0.2

SECT. Z-Z

Technical drawing of a U-shaped part. The width is 1.69 ± 0.3 . The height is 1.37 ± 0.3 . The fillet radius is $OR \ \varnothing.4$.

SECT. Y-Y

1. 適合ハウジング：51022 シリーズ
APPLICABLE HOUSING : 51022 SERIES
2. メッキ仕様 PLATING
錫 0.9μm MIN. リフロー処理 (前メッキ)
TIN 0.9μm MIN. REFLOW TREATMENT (PRE-PLATED)

角度	ANGLE
30 以上	OVER 30
10 以上 30 未満	OVER 10 UNDER 30
10 未満	UNDER 10
一般公差 GENERAL TOLERANCES	

8				
25	E	変更 REVISED	(J30697)	H.H. M.
2	D	変更 & 再作図 REVISED & REDRAWN	(J20810)	H.H. M.
記号 TR		変更内容 REVISION RECORD		DR. CHK

材料 MATERIAL	リン青銅 PHOSPHOR BRONZE ($\tau=0.15$)
仕上げ FINISH	—H—
適用電線範囲 WIRE RANGE	AWG #28-32
被覆外径 INS. RANGE	$\varnothing 0.5-1.0$
DRAWN BY 92/10/22 H.HIRAMOTO	CHK'D BY 93/1/2 H.HIRAMOTO
APP'D BY 93/1/3 M.FUKUSHIMA	尺度 SCALE 20 -

50061-8100	バラ状 LOOSE
50061-8000	連鎖状 CHAIN
ENG. NO.	端子形状 FORM

 MOLEX-JAPAN CO.,LTD. 日本モレックス株式会社		
REVISE ONLY ON CAD SYSTEM		
TITLE 名称 I.25 BOARD IN CRIMP TERMINAL		
DWG. NO. SD-50061-8*00		REV E

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX(JAPAN) AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
 本図面は日本モレックス(株)の所有する情報を含むもので当社の許可なく複製を禁止する。 EN-01C(032)MXJ-32