



4280




4280-0-XX-XX-16-XX-10-0
Solder mount in $\varnothing.067 \pm .003$ PTH.
#16 Contact for $\varnothing.022-.034$ pins.
Also available on 8mm wide carrier
tape: 6,000 parts per 13" reel.

5280




5280-0-XX-XX-16-XX-40-0
Solder mount in $\varnothing.067 \pm .003$ PTH.
#16 Contact for $\varnothing.022-.034$ pins.
Also available on 16mm wide carrier
tape: 2,200 parts per 13" reel.

0479




0479-0-XX-XX-34-XX-10-0
Solder mount in $\varnothing.077 \pm .003$ PTH.
#34 Contact for $\varnothing.032-.046$ pins.
Also available on 16mm wide carrier
tape: 2,000 parts per 13" reel.

0379




0379-0-43-XX-34-XX-10-0
Solder mount in $\varnothing.077 \pm .003$ PTH.
#34 Contact for $\varnothing.032-.046$ pins.

9873




9873-0-XX-XX-02-XX-10-0
Solder mount in $\varnothing.083 \pm .003$ PTH.
#02 Contact for $\varnothing.040-.050$ pins.
Also available on 12mm wide carrier
tape: 4,500 parts per 13" reel.

5364




5364-0-XX-XX-23-XX-10-0
Solder mount in $\varnothing.103 \pm .003$ PTH.
#23 Contact for $\varnothing.045-.065$ pins.
Also available on 12mm wide carrier
tape: 2,000 parts per 13" reel.

5291



5291-0-XX-XX-08-XX-40-0
Solder mount in $\varnothing.139 \pm .003$ PTH.
#08 Contact for $\varnothing.084-.102$ pins.
Also available on 16mm wide carrier
tape: 1,700 parts per 13" reel.

3966



3966-0-XX-XX-07-XX-10-0
Solder mount in $\varnothing.135 \pm .003$ PTH.
#07 Contact for $\varnothing.065-.082$ pins.
Also available on 24mm wide carrier
tape: 650 parts per 13" reel.

SPECIFICATIONS

SHELL MATERIAL:
Brass Alloy 360, 1/2 Hard
CONTACT MATERIAL:
Beryllium Copper Alloy 172, HT
SOLDER BARRIER:
Organic Fibre Plug®
DIMENSION IN INCHES
TOLERANCES ON:
LENGTHS: $\pm .005$
DIAMETERS: $\pm .002$
ANGLES: $\pm 2^\circ$

ORDER CODE: XXXX - 0 - XX - XX - XX - XX - X0 - 0

BASIC PART #

SPECIFY PACKAGING:
43 Discrete Receptacles
67 Supplied on 13" Reels

SPECIFY SHELL FINISH:
01 200 μ " TIN/LEAD OVER NICKEL
80 200 μ " TIN OVER NICKEL

SPECIFY CONTACT FINISH:

27 30 μ " GOLD OVER NICKEL
01 200 μ " TIN/LEAD OVER NICKEL
80 200 μ " TIN OVER NICKEL

CONTACT #

See page 203 for alternates available

