


RECOMMENDED P.C.B. LAYOUT



CIRCUIT: SPDT

CONTACT CONFIGURATION

SWITCH FUNCTION	
PDS. 1	PDS. 2
DN	DN
2-1	2-3

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NOS. FOR REFERENCE ONLY.
  4. CONTACT RATING: 0.4 VOLT-AMPS(VA) MAX@20V MAX (AC OR DC)
  5. FIXED TERM & MOVING CONTACT:  
COPPER ALLOY W/GOLD PLATE OVER NICKEL PLATE
  6. CONTACT RESISTANCE: 50MΩ MAX
  7. MECHANICAL LIFE: 20,000 OPERATIONS
  8. INSULATION RESISTANCE: 1000 MΩ UNDER 500V
  9. OPERATING TEMP: -40°C TO 85°C
  10. BREAKING CAPACITY: 400 MA 20V

REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	11718	RELEASED FOR PRODUCTION	10/09/01	CJC

TITLE	SCALE	DATE	DR	DWG	REV
600 SP-1 S1 M3 R E	2:1	10/09/01	CJC	T611007	A



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED