


600N Series

Tubeaxial

60x60x25mm



■ DC fans with electronically commutated external rotor motor. Fully integrated commutation electronics.

■ With electronic protection against reverse polarity, blocking and overloading.

■ Mounting from either face using four 4.3 mm holes.

■ Fan of fiberglass reinforced plastic. PBTP housing, PA impeller.

■ Air exhaust over struts. Rotational direction CCW looking at rotor.

■ Electrical connection via 2 leads AWG 22, TR 64. Stripped and tinned ends.

■ UL, CSA, VDE approvals on some models, please contact application engineering.

Part Number	CFM @ 0	Curve	Volts	Voltage Range	Power (W)	dBA	Max Ambient Temp C	Wgt. (lbs)	Type Of Bearing	Features
612NL	12	1	12	8 to 15	0.6	16	70	0.19	Ball	Leads
612NML	14	2	12	8 to 15	0.8	19	70	0.19	Ball	Leads
612NM	20	3	12	8 to 15	1.1	28	70	0.19	Ball	Leads
612NN	24	4	12	8 to 15	1.6	35	70	0.19	Ball	Leads
612NH	27	5	12	8 to 15	2.0	38	70	0.19	Ball	Leads
614NL	12	1	24	18 to 28	0.9	16	70	0.19	Ball	Leads
614NML	14	2	24	18 to 28	1.0	19	70	0.19	Ball	Leads
614NM	21	3	24	18 to 28	1.4	28	70	0.19	Ball	Leads
614NN	24	4	24	18 to 28	1.8	35	70	0.19	Ball	Leads
614NH	27	5	24	18 to 26	2.1	38	70	0.19	Ball	Leads
614NHH	33	6	24	18 to 26	3.0	43	70	0.19	Ball	Leads
618NN	24	4	48	36 to 56	2.1	35	65	0.19	Ball	Leads

