



PRODUCT NO	NO OF POS	DIM L	DIM K	POSITIONS POLARIZED		PLATING	LF OPTION
				ROW - A	ROW - B		
65895-001	2X12	1.480/37.59	1.100/27.94	6,7	6,7	30μ"/.76μ Au OVER 50μ"/1.27μ Ni	↑
↑ -002	2X20	2.280/57.91	1.900/48.26	19	NONE	↑	
-003	2X26	2.880/73.15	2.500/63.50	6,7,13,14,17,20,21	6,7,13,14,20,21	↑	
-004	2X5	.780/19.81	.400/10.16	NONE	NONE	↓	
-005	2X5	.780/19.81	.400/10.16	NONE	3		
-006	2X12	1.480/37.59	1.100/27.94	6,7,8	3,6,7	30μ"/.76μ Au OVER 50μ"/1.27μ Ni	
-007	2X5	.780/19.81	.400/10.16	NONE	NONE	120μ"/3.05μ TIN OVER 50μ"/1.27μ Ni	
-008	2X12	1.480/37.59	1.100/27.94	1,6,7	6,7,10	30μ"/.76μ Au OVER 50μ"/1.27μ Ni	
-009	2X15	1.780/45.21	1.400/35.56	NONE	NONE	↑	
-010	2X12	1.480/37.59	1.100/27.94	6,7	3,6,7,11		
-011	2X13	1.580/40.13	1.200/30.48	NONE	NONE		
-012	2X20	2.280/57.91	1.900/48.26	NONE	NONE		NOTE 5
-013	2X25	2.780/70.61	2.400/60.96	NONE	NONE		
-014	2X6	.880/22.35	.500/12.70	NONE	NONE	↓	
-015	2X17	1.980/50.29	1.600/40.64	NONE	NONE	30μ"/.76μ Au OVER 50μ"/1.27μ Ni	
-016	2X12	1.480/37.59	1.100/27.94	6,7	6,7	30μ"/.76μ GXT OVER 50μ"/1.27μ Ni	
-017	2X20	2.280/57.91	1.900/48.26	19	NONE	↑	
↓ -018	2X26	2.880/73.15	2.500/63.50	6,7,13,14,17,20,21	6,7,13,14,20,21		
-019	2X5	.780/19.81	.400/10.16	NONE	NONE		
-020	2X5	.780/19.81	.400/10.16	NONE	3		
-021	2X12	1.480/37.59	1.100/27.49	6,7,8	3,6,7		
-022	2X12	1.480/37.59	1.100/27.94	1,6,7	6,7,10		
-023	2X15	1.780/45.21	1.400/35.56	NONE	NONE		
-024	2X12	1.480/37.59	1.100/27.94	6,7	3,6,7,11		
-025	2X6	.880/22.35	.500/12.70	NONE	NONE	↓	
-026	2X25	2.780/70.61	2.400/60.96	NONE	NONE		
65895-027	2X20	2.280/57.91	1.900/48.26	NONE	NONE	30μ"/.76μ GXT OVER 50μ"/1.27μ Ni	↓

mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY		 www.fciconnect.com				
ltr	ecn no	dr	date	linear	.XX±.01/.X±.3				title				
N					.XXX±.005/.XX±.13				.100 X .100 RT HDR ASS'Y				
					.XXX±.0020/.XXX±.051								
				angles	0° ±2°				product family HEADERS				
				dr	E J HALEY	6-22-87			size		code		
				engr	R FROST	6-22-87			dwg no		213		
				chr	R FROST	6-22-87		scale	A		sheet		
				appd	R FROST	6-22-87			65895		2 of		
sheet index	revision sheet												

PRODUCT NUMBER
SEE TABLE

NOTES

1. HOUSING MATERIAL:
20% GLASS FILLED POLYESTER, THERMOPLASTIC.
FLAME RETARDANT PER UL 94V-0. COLOR: BLACK

THIS PRODUCT WILL WITHSTAND EXPOSURE TO 260° C
TEMPERATURE FOR 15 SECONDS IN A WAVE SOLDER
APPLICATION WITH A .60 [1.5mm] THICK PCB.
- ② TERMINAL MATERIAL: PHOS BRONZE
PLATING ON TIP OPTIONAL.
3. 1° MAX DRAFT PERMITTED ON ALL SURFACES
UNLESS OTHERWISE SPECIFIED.
4. GXT PLATED, PRODUCT HAS GOLD FLASH.
5. ADD SUFFIX LF AT END OF PART NUMBER FOR
LEAD FREE OPTION.
6. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES
AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN
GS-22-008.
7. THIS PRODUCT MAY HAVE 100% TIN PLATING IN THE
INTERFACE AND HAS NOT BEEN TESTED FOR WHISKER
GROWTH IN ALL INTERCONNECT ENVIRONMENTSS.

mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY		A FCI www.fciconnect.com				
ltr	ecn no	dr	date	linear	.XX±.01/.X±.3			projection 	title .100 X .100 RT HDR ASS'Y				
N					.XXX±.005/.XX±.13								
					.XXX±.0020/.XXX±.051								
				angles	0° ±2°			INCH/MM ← →	product family HEADERS				code
				dr	E J HALEY	6-22-87	size dwg no				213		
				enrg	R FROST	6-22-87							
				chr	R FROST	6-22-87							
				appd	R FROST	6-22-87	scale 1:1	A	65895				sheet 3 of
sheet index	revision sheet												