



CrimplokTM 6900 SC Connector

Technical Report

1.0 Product Description & Requirements

The 3M Crimplok™ SC Connector is designed to provide the customer with an easily installed, high performance, low-cost, epoxy-free, pull-proof multimode connector for use in indoor applications, such as local area networks. The main advantage of this connector is its ability to give the customer a lower installed cost due to time saved at installation with a minimal initial investment in tooling.

Some mechanical connectors grip the fiber buffer coating which results in poor performance characteristics in initial insertion loss measurements, as well as during temperature cycling. Reliability of this method is also questionable due to differences in buffer coating materials encountered with different manufacturers and the tolerances involved. Some mechanical connectors grip the glass portion of the fiber with soft compliant materials, such as plastics, which have demonstrated poor performance characteristics at initial insertion loss and during temperature cycle testing. Reliability is again questionable due to the nature of the materials involved, which provide the grip onto the glass fiber.

The 3M Crimplok™ SC Connector grips the glass fiber with a small metallic element that is integrated inside the backbone of the SC connector version. Activation of the element is achieved by depressing an element cap located in the SC backbone. The activation tool, which is part of the new kit, activates the element cap and secures the fiber. The tool also sets the amount of fiber protrusion within strict tolerance limits, at the end of the ferrule for faster polishing times. The connector is removed, and a simple one-step polish is performed on a fine grit abrasive paper that requires less than 30 seconds to complete. The connector is now ready for use.

2.0 Test Program

The purpose of the test program is to assess the long-term performance of the 3M Crimplok™ SC™ Fiber Optic connector. A series of optical, environmental and mechanical tests were conducted which exposes them to conditions more severe than those anticipated in actual use. All tests are performed in accordance with TIA-568A. Field mount Crimplok connectors in the evaluation were obtained directly from 3M factory stock, assembled on cable, and spliced into the test system. A list of tests performed is presented below.

New Product	Environmental Group 0	Mechanical Group 1	Mechanical Group 2
New Product	Cold Temperature Life Humidity	Impact Flex Twist Cable Retention	Vibration Connector Durability Connector Intermatability

Sample Preparation:

The Crimplok™ SC Connectors were cleaved using the Model 6955-T Crimplok Activation Tool, and were processed according to the Crimplok Instruction Manual P/N 78-8073-7660-9, Issue 2, July 1997. The fiber protrusion specification after cleaving is 105 ± 25 mm (using the 6955-T Activation Tool), and the final fiber protrusion specification after polishing is 10-50 mm (typical values range from 15-40 mm.)

The Crimplok™ SC Connectors tested in this report had a fiber protrusion range of 95-122 mm after cleaving, and the final fiber protrusions after polishing were:

Mean = 28.6 mm
Sigma = 4.6 mm
Min. = 22.0 mm
Max. = 40.0 mm

2.1 New Product

Procedure:

The plugs and couplings for pretest measurements were cleaned as described in section 1.7.4 of the TIA-568A. Measurements of loss and return loss at wavelengths of 850 nm and 1310 nm were performed at ambient conditions before any environmental testing.

Sample Size: 30

Results:

Wavelength	Loss (dB)		Return Loss (dB)	
	Mean	Std. dev.	Mean	Std. dev.
850	0.11	0.07	-27.8	3.1
1310	0.13	0.06	-28.9	1.6

2.2 Cold (Group 0)

Procedure:

Measurements of loss and return loss at 850 nm and 1310 nm wavelengths are performed at the start and the finish of the test at 22°C. The test samples are subjected to 96 hours (4 days) at -10°C. Additional measurements are made every 15 minutes at -10°C during test to monitor performance.

Sample Size: 10

Results:

LOSS (db)						
Wavelength	Initial Mean	Initial Std. dev.	Mean during	Std. dev. during	Mean Final	Std. Dev. Final
850	0.11	0.07	0.16	0.06	0.16	0.06
1310	0.13	0.06	0.10	0.05	0.11	0.06

RETURN LOSS (db)						
Wavelength	Initial Mean	Initial Std. dev.	Mean during	Std. dev. during	Mean Final	Std. Dev. Final
850	-27.8	3.1	-31.40	1.64	-31.32	1.73
1310	-28.9	1.6	-31.32	0.67	-28.32	0.70

2.3 Temperature Life (Group 0)

Procedure:

Testing is performed on samples after exposure to the Cold test. Measurements of loss and return loss at 850 nm and 1310 nm wavelengths are performed at the start and the finish of the test at 22°C. The test samples are subjected to 336 hours (14 days) at 60°C. Additional measurements are made every hour at 60°C during test to monitor performance.

Sample Size: 10

Results:

LOSS (db)						
Wavelength	Initial Mean	Initial Std. dev.	Mean during	Std. dev. during	Mean Final	Std. Dev. Final
850	0.16	0.06	0.17	0.06	0.17	0.06
1310	0.10	0.05	0.12	0.05	0.12	0.06

RETURN LOSS (db)						
Wavelength	Initial Mean	Initial Std. dev.	Mean during	Std. dev. during	Mean Final	Std. Dev. Final
850	-31.25	1.72	-31.76	1.77	-30.72	1.88
1310	-28.10	0.68	-27.70	1.00	-27.64	1.08

2.4 Humidity (Group 0)

Procedure:

Testing is performed on samples after exposure to the temperature life test. Measurements of loss and return loss at 850 nm and 1310 nm wavelengths are performed at the start and the finish of the test at 22°C, and every 15 minutes during the test at 40°C with 90%-95% relative humidity.

Sample Size: 10

Results:

LOSS (db)						
Wavelength	Initial Mean	Initial Std. dev.	Mean during	Std. dev. during	Mean Final	Std. Dev. Final
850	0.17	0.06	0.17	0.06	0.18	0.06
1310	0.12	0.06	0.11	0.06	0.13	0.06

RETURN LOSS (db)						
Wavelength	Initial Mean	Initial Std. dev.	Mean during	Std. dev. during	Mean Final	Std. Dev. Final
850	-31.12	1.72	-30.72	1.68	-31.00	1.76
1310	-28.19	0.82	-27.71	0.80	-27.97	0.87

3.0 Mechanical Tests (Group 1)

3.1 Impact

Procedure:

The connector is placed in the impact test fixture. The connector is raised to the horizontal position and released in a manner so that it struck a concrete block. This was repeated 8 times, then cleaned and measured for loss and return loss. The connector is also inspected for any physical damage.

Sample Size: 10

Results:

Wavelength	Loss (dB)		Return Loss (dB)	
	Mean	Std. dev.	Mean	Std. dev.
850	0.17	0.08	-27.29	0.70
1310	0.31	0.09	-30.86	1.98

3.2 Flex

Procedure:

Testing was performed on samples subjected to the Impact test. The connector - coupling is mounted onto the swingarm of the 3M Flex Tester. A 0.5 kg load is attached to the cable 25 cm from the pivot point. The connector is then cycled through 0°, +90°, 0°, -90°, 0° about the center axis of the connector for 100 cycles. At the completion of the test, the connector is measured for insertion loss and return loss.

Sample Size: 10

Results:

Wavelength	Loss (dB)		Return Loss (dB)	
	Mean	Std. dev.	Mean	Std. dev.
850	0.14	0.09	-26.68	1.98
1310	0.26	0.10	-30.81	0.70

3.3 Twist

Procedure:

Testing was performed on samples subjected to the Flex test. The connector - coupling is mounted onto the swingarm of the 3M Flex Tester and the swingarm is locked in the 0° position. A 15 N (3.3 lbs.) load is attached to the cable 25 cm from the pivot point. The weight is rotated about the cable axis 2.5 revolutions in one direction, reversed for 5 revolutions, and reversed again 5 more revolutions for a total of 10 cycles. At the completion of the test, the connector is measured for insertion loss and return loss.

Sample Size: 10

Results:

Wavelength	Loss (dB)		Return Loss (dB)	
	Mean	Std. dev.	Mean	Std. dev.
850	0.15	0.06	-26.91	0.95
1310	0.22	0.09	-30.57	0.69

3.4 Cable Retention

Procedure:

Testing was performed on samples subjected to Twist test. A coupling was secured to the traversing stage of an Instron tensile tester. At 0.3 m from the coupling - connector, the cable was secured to the stationary base by wrapping the cable 3 times around a 3" mandrel. A load of 15 lbs. (67 N) @ 0° is applied to the connector for 5 seconds, then released. Additional testing was performed after the first cable Retention Test in the same manner, but with 4.5 lbs. (20 N) @ 90°. Values for insertion loss and return loss are measured 10 seconds after releasing the load.

Sample Size: 10

Results:

(Cable Retention 15 lbs. @ 0°)

Wavelength	Loss (dB)		Return Loss (dB)	
	Mean	Std. dev.	Mean	Std. dev.
850	0.12	0.08	-26.76	0.84
1310	0.25	0.10	-30.49	0.85

(Cable Retention 4.5 lbs. @ 90°)

Wavelength	Loss (dB)		Return Loss (dB)	
	Mean	Std. dev.	Mean	Std. dev.
850	0.14	0.09	-26.81	0.80
1310	0.26	0.07	-30.52	0.80

4.0 Mechanical Tests (Group 2)

4.1 Vibration

Procedure:

Ten samples from group 2 were subjected to a vibration test from 10 to 55 Hz, 1.5 mm p-p amplitude. The samples were attached to the vibration table via a 10 port patch panel. The connectorized samples were tested in 3 axis (X, Y, Z) for 2 hours in each axis, at a sweep rate of 45 Hz per minute.

Sample Size: 10

Results:

(Loss dB)

Wavelength	Initial		After Vibration	
	Mean	Std. dev.	Mean	Std. dev.
850	0.06	0.03	-24.38	1.19
1310	0.13	0.06	-27.52	0.88

(Return Loss dB)

Wavelength	Initial		After Vibration	
	Mean	Std. dev.	Mean	Std. dev.
850	0.04	0.04	-24.35	1.33
1310	0.13	0.08	-27.42	0.96

4.2 Connector Durability

Procedure:

After the completion of the vibration test, the 10 samples from group 2 were subjected to a connector durability test to 500 insertions. One side of each of the connectorized samples was removed and inserted 500 times. Cleaning and measurements were performed every 25th insertion.

Sample Size: 10

Results: (Loss dB)

Wavelength	Initial		After Connector Durability	
	Mean	Std. dev.	Mean	Std. dev.
850	0.04	0.04	0.06	0.04
1310	0.13	0.08	0.15	0.07

(Return Loss dB)

Wavelength	Initial		After Connector Durability	
	Mean	Std. dev.	Mean	Std. dev.
850	-24.35	1.33	-23.93	0.93
1310	-27.42	0.96	-27.50	0.89

4.3 Connector Intermatibility

Procedure:

This test is not a requirement of TIA-568A and is performed to demonstrate compatibility of the Crimplok connector to standard epoxy connectors. After completion of the Connector Durability test, the 10 samples from group 2 were subjected to a connector intermatibility. One side of each connectorized samples was removed and mated to a 3M Epoxy factory mount SC connector, then removed and inserted 10 times. Cleaning and measurements were performed after every insertion.

Sample Size: 10

Results:

Wavelength	Loss (dB)		Return Loss (dB)	
	Mean	Std. dev.	Mean	Std. dev.
850	0.06	0.04	-24.0	1.06
1310	0.15	0.07	-27.6	1.07

5.0 Conclusion

Throughout this test program the 3M™ Crimplok™ SC™ fiber optic connector met or exceeded all targeted performance requirements. The excellent test results demonstrate the low insertion loss, environmental stability and physical robustness of this optical fiber termination method. This connector will ensure a reliable voice and/or data transmission circuit.

For information concerning specific agency approvals, please contact your 3M Telecom Systems Division representative.

Important Notice

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained herein are made in lieu of all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS.



Telecom Systems Division

6801 River Place Blvd.
Austin, TX 78726-9000
800/426-8688



*Recycled paper
50% pre-consumer
10% post-consumer*

Litho in USA
© 3M 1998 78-8110-6480-3-A