

7334L2622F02LF

Catalogue Part Number Key

Lead Free Version (Optional)

Durability
0: 2500 Mating Cycles
2: 10000 Mating Cycles
5: 100000 Mating Cycles

Number of contacts :
2: 8 contacts ISO
3: 16 contacts ISO + AFNOR

GENERAL:
This L26 connector uses a "sliding" contact technology suitable for most applications.
It has been designed for easy mounting on the PCB.

ELECTRICAL PROPERTIES:
Insulation resistance : 5000 MΩ min
Dielectric withstanding : 750 Vrms min
Current carrying capacity : 10µA min. 1A max
Contact resistance : 100mΩ max
Card sensor type : Normally closed

MECHANICAL PROPERTIES:
Contact Normal force : 0.6 N max (EMV Standard)
Insertion force : 10 N max
Extraction force : 1 N min
Durability : According to UTE C93-421

MATERIAL:
Housing : Thermoplastic 30 % Glass Filled, Colour Black, Rated UL94V0
Contacts and switch : Phosphor bronze
Plating : Nickel all over on contact area
Gold on contact area.
Tin/Lead on soldertails

FOR LEAD FREE PLATING :
Matte Tin on solder tail in place of Tin/Lead
Bare edge allowed

ENVIRONMENT:
Operating temperature: -20°C / +70°C
Storage temperature: -40°C / +85°C
Printed Circuit Board thickness : 1.6mm

REFERENCE DOCUMENTS:
Product specification VGN 11596
Packaging Specification VGN 11619


LEAD FREE VERSION:

"This product meets European Union Directives and other country regulations as described in GS-22-008"

The housing will withstand exposure to 260°C peak temperature for 10seconds in a wave solder application with a 1.6mm minimum thick circuit board.
Use protective adhesive tape (Kapton or Teflon) or protective metallic devices on the areas which are directly exposed to wave soldering as it is used in classical leaded wave soldering

General Tolerances: ± 0.2 mm

rev	ecn no	dr	date
A	F20307	DLE	2002/04/30
B	Is 3053	JTA	2003/05/13
C	105-0071	DTK	2005/06/25
D	106-0084	SSC	2006/06/21
E	106-0189	SSC	2006/10/17
-	-	-	-
-	-	-	-

www.fciconnect.com			surface - 		tolerance std ISO 1302 ISO 406 ISO 1101		projection 			
			TOLERANCES UNLESS OTHERWISE SPECIFIED							
Dr	N.TWENCY	2002/04/30	ANGULAR	LINEAR	0.X	±	size A3	Scale 3:2		
Eng	F TISSERAND	2002/04/30			0.XX	±				
Chr	DILIPTHOMAS	2006/10/17			0.XXX	±				
Appr	K.V.SIVADAS	2006/10/17	0°	±°	Product family		5S2F	ECN	106-0189	
								Spec ref	SEE NOTES	
			title L26 TYPE F02			dwg no VJW_54702			Rev E	
			catalog no			CUSTOMER			sheet 1 of 2	
			SEE TABLE							




L26 TYPE F02





catalog no

SEE TABLE

CUSTOMER



SCALE 1:1



[illegible]

Hatching area might be free of components
Maximum free space outside of these zones = 5.5 mm

46

$\varnothing 10^{+0,1}_0$

10 holes

47

$\varnothing 0,1$ A B

C1 C2 C3 C4

S1 S2

A

B

C5 C6 C7 C8


$3 \times 2,54 = 7,62$

48

49


SCALE 3:2

CARD
INSERTION



ECHELLE 1:1

EUROPEAN PROJECTION

www.fciconnect.com			surface - 		tolerance std ISO 1302 ISO 406 ISO 1101		projection 		mm 		
			TOLERANCES UNLESS OTHERWISE SPECIFIED								
Dr	N.TWENCY	2002/04/30	ANGULAR	LINEAR	0.X	±	size A3	Scale 3:2			
Eng	F.TISSERAND	2002/04/30			0.XX	±					
Chr	DILIPTHOMAS	2006/10/17			0.XXX	±					
Appr	K.V.SIVADAS	2006/10/17	Product family				5S2F	Spec ref	SEE NOTES		
		title L26 TYPE F02 --				dwg no VJW_54702				Rev. E	
		catalog no				SEE TABLE		CUSTOMER		sheet 2 of 2	