




1 2 3 4

PRODUCT NUMBER
SEE TABLE

SPECIFICATIONS	MATERIALS
SHIELD	HIGH STRENGTH COPPER ALLOY
HOUSING	THERMOPLASTIC : UL 94V-O RATED WHITE
TERMINAL	HIGH STRENGTH COPPER ALLOY
	PLATING
SHIELD	FOR 73450-001/001LF: 80 MICROINCHES Tin OVER 30 MICROINCHES NICKEL FOR 73450-002/002LF: 50 MICROINCHES NICKEL PLATING FOR 73450-003/003LF: 80 MICROINCHES TIN (DULL APPEARANCE) OVER 30 MICROINCHES NICKEL
TERMINAL	CONTACT AREA : 30 MICROINCHES GXT TAIL AREA : 100 MICROINCHES TIN/LEAD FOR 73450-00X 100 MICROINCHES TIN FOR 73450-00XLF UNDERPLATE : 40 MICROINCHES NICKEL
	ELECTRICAL
VOLTAGE RATING	40VDC
CURRENT RATING	1.5 A AT ONE CONTACT
DIELECTRIC WITHSTANDING VOLTAGE	500VDC
INSULATION RESISTANCE	100 MEGAOHMS AT 500VDC

mat'l code SEE NOTES				tolerances unless otherwise specified		CUSTOMER COPY		 Electronics www.fciconnect.com			
ltr	ecn no.	dr	date	linear	.X ±.3	projection 	title P1394 ASSEMBLY	product family P1394 code 213			
G					.XX ±.20						
					.XXX ±.100						
				angles	0° ±2°	 MM scale 4:1	A	dwg no 73450 sheet 2 of 2			
			dr	G.PETERS 12/4/97							
			enrg	R.MACMULLIN 12/4/97							
			chr	R.MACMULLIN 12/4/97							
			appd	R.MACMULLIN 12/4/97							
sheet index	revision index										

THIS FILE WAS ORIGINALLY CREATED IN THE PRO ENGINEER ENVIRONMENT AND ANY FUTURE REVISIONS TO THIS FILE MUST BE MADE IN THE PRO ENGINEER ENVIRONMENT

form no. 7530-001-103

3 4

cage code
22526

PDM: Rev:G

STATUS:Released

Printed: Feb 06, 2008