








FCIconnect.com

Copyright FCI

PRODUCT NUMBER  
SEE SHT. 2



mat'l. code				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101	projection  INCH/MM scale 1:1	product family LATCH-N-LOK	
ltr	ecn no	dr	date	tolerances unless otherwise specified				title	
D	V91916	TGD	10/7/99	angles		.XX±.01/.3		1X8 LATCH-N-LOK 360° SHIELDED	
E	V92065	RGD	10/29/99	linear		.XXX±.005/.13		PLUG CONN. KIT W/O PV'S	
F	V01017	TFG	5/15/00	0°±2°		.XXXX±.0020/.051			
G	V01050	TFG	6/5/00	dr	M. HERNANDEZ	12/03/04		dwg no	sheet 1 of 3 size
H	V01093	TFG	7/6/00	enrg	M. BARRIOS	12/03/04		74903	A3
J	M04-0229	MHT	12/03/04	chr	M. BARRIOS	12/03/04			
K	M06-0365	AGS	9/20/06	appd	M. BARRIOS	12/03/04			
sheet	revision	K	K	K				type Product Customer Drawing	
index	sheet	1	2	3					



74903-TUVLF


U	COLOR	
01	LT-GRAY	OBS
02	OFF WHITE	
03	DK- GRAY	OBS
04	BLACK	
05	SLATE-GRAY	OBS
07	SILVER GRAY	
08	PEARL- WHITE	OBS
09	PEBBLE GRAY	

T	HOLE DIA.
7	.265/6.73
9	.312/7.92


### EXAMPLE

74903-707LF: IS A 1x8 REAR EXIT PLUG  
IN SILVER GRAY WITH A CABLE EXIT  
HOLE SIZE OF .265 [6.73] CABLE RANGE ,


mat'l. code				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection 		product family LATCH-N-LOK			
ltr	ecn	no	dr	date	tolerances unless otherwise specified				INCH/MM scale 1:1	title 1X8 LATCH-N-LOK 360° SHIELDED PLUG CONN. KIT W/O PV'S dwg no 74903 sheet 2 of 3 size A3 type Product Customer Drawing			
K					angles	linear	.XX±.01/.3 .XXX±.005/.13 .XXXX±.0020/.051						
					0'±2'								
					dr	M. HERNANDEZ	12/03/04						
				enr	M. BARRIOS	12/03/04							
				chr	M. BARRIOS	12/03/04							
				app	M. BARRIOS	12/03/04							
sheet index	revision sheet												



REAR CAP




MINI  
LATCH  
HOUSING



TOP  
SHIELD



BOTTOM  
SHIELD



PLUG FRONT

NOTES:

- ① EACH KIT CONTAINS ONE EACH OF THE FOLLOWING COMPONENTS  
LATCH-N-LOK PLUG  
LATCH-N-LOK END CAP  
MINI LATCH HOUSING  
360° SHIELD CANS.
2. COMPONENTS ARE BULK PACKAGED WITH 100 pcs. OF A COMPONENT PER BAG. PVC's MUST BE ORDERED SEPARATELY.
3. MATERIALS USED: PLUGS AND CAPS ARE MOLDED IN POLYCARBONATE. THE MINI LATCH HOUSING ARE MOLDED IN NYLON. COLOR IS BLACK. THE SHIELD CAN IS 3/4 HARD BRASS PLATED WITH 2.5um MIN. BRIGHT TIN. 1.0um MIN. NICKEL UNDERPLATE.
- ④ DIMENSIONS ARE APPROXIMATE AND REFLECT PLUG IN UNLATCHED STATE.
5. PART NUMBERS WITH LF IN THE END ARE LEAD FREE.
6. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.

mat'l. code				surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection 	product family LATCH-N-LOK
ltr	ecn	no	dr	date	tolerances unless otherwise specified	INCH/MM scale 1:1 	title
K					angles .XX±.01/.3 linear .xxx±.005/.13 0'±2' .xxx±.0020/.051		1X8 LATCH-N-LOK 360° SHIELDED PLUG CONN. KIT W/O PV'S
					dr M. HERNANDEZ 12/03/04 enr M. BARRIOS 12/03/04 chr M. BARRIOS 12/03/04 appd M. BARRIOS 12/03/04		dwg no 74903 sheet 3 of 3 size A3
sheet index	revision sheet						type Product Customer Drawing