

FClconnect.com

3 I

PRODUCT NUMBER NOTE 9	PLATING	UNDERPLATING
76151-YYY	30μ" [0.76μ] MIN Au	50μ" [1.27μ] MIN Ni
76151-YYYLF	30µ [0.76µ] MIN Ad	30μ [1.27μ] MIIN NI
76153-YYY	50" [1 27] MINI A	EO" [1 07] MINI NI
76153-YYYLF	50μ" [1.27μ] MIN Au	50μ" [1.27μ] MIN Ni
76154-YYY -	120µ" [3.05µ] MIN 93/7 SnPb	50μ" [1.27μ] MIN Ni
76154-YYYLF	100μ" [2.54μ] MIN Sn (NOTE 10)	50μ" [1.27μ] MIN Ni
76155-YYY	70. " [0.70.] MINI OVE IM	EO " [4 07] MINI NI
76155-YYYLF	30μ" [0.76μ] MIN GXT™	50μ" [1.27μ] MIN Ni
76156-YYY	45 " [0 70] MINI OVI IM	EO" [4 07] MINI NI
76156-YYYLF	15µ" [0.38µ] MIN GXT™	50μ" [1.27μ] MIN Ni
76159-YYY	45 " [O 70] MINI A	FO " [4 07] MINI NI
76159-YYYLF	15μ" [0.38μ] MIN Au	50μ" [1.27μ] MIN Ni

1 | 2

1

NOTES:

- 1.) MATERIAL: 3/4 HARD PHOS BRONZE ASTM B-159-66
- (2.) BURNISH MARKS ON PIN PERMITTED BURR .003 [0.08] MAX BULGE .0005 [0.013] MAX TYP.
- 3. SEE PRODUCT SPECIFICATION BUS-12-064 FOR P.C. BOARD HOLE DIAMETER AND P.C. BOARD HOLE PLATING INFORMATION.
- (4.) .002 [0.05] R MAX TYP 4X ON WIRE PORTION OF PIN.
- (5.) TWO SIDES OF LEAD-IN NOT PLATED TYP BOTH ENDS.
- 6. .016 [0.41] MAX OPPOSITE END IF DIM B IS LESS THAN .230 [5.84].
- (7.) TOLERANCE: +.001 [0.03], -.002 [0.05]
- (8.) TOLERANCE: ±.001 [0.03]
- 9. ADD AN LF SUFFIX TO PART NUMBERS FOR PRODUCT THAT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- (10) THIS PRODUCT HAS 100% TIN PLATING IN THE INTERFACE AND HAS NOT BEEN TESTED FOR WHISKER GROWTH IN ALL INTERCONNECT ENVIRONMENTS.

mat	'l. code	2		surfa	e		toler	ance		proje	ection		prod	luct f	amily							
	SE	E NOT	E 1	ASME	Y14.5	\vee	ASME	Y14.5		d	5	1			ΡI	NF	ROD	UCT	S			
ltr	ecn r	no dr	date	tolerar	ices u	nless	otherw	ise sp	ecified	Q	7 -	J	title									
AA				— angle	JF.		.XX±.01/.X			INCH/M		INCH/MM		BERGPIN® LOOSE PIEC						FCF	:F	
				arigic	near near	Х	XX±.00	5/.XX±	.13	-	,	_	ļ '						. SI		-	
				0° ±3	2* _	XXX.	(X±.002	0/.XXX	±.051	scale	2 1	:1		.03) 9 [0.9	9]	DIA.	. SI	ΑK		
				dr	М.	FETR	:OW	1994-	-05-16	_			dwg	ΠO			S	heet	2 0	f 5	size	
				engr	L	. FY		1994-	-05-16	FCI			76151						l _{A4}			
				chr	L	. FY		1994-05-1		•				701		13	131			<u> </u>		
				appd	L	. FYI	Ę	1994-	-05-16		~		type				CUS	STOM	IER [Draw	/ing	
she	et	revision																				
inde	∘х Г	sheet																				

3

form: A4mmXLc

- DISCONTINUED

PDM: Rev:AA

STATUS: Released

Printed: Sep 24, 2008

		Copyright FCL					FCI						
				1 2		FCId	connect.com			3		4	
	PRODUCT NO. NOTE 9	CONTACT AREA DIM "A"	TERMINATION AREA DIM "B"	DIM '	"C"	DIM "H" FOR .062 BOARD 1.57	DIM "H" FOR .093 BOARD 2.36	DIM "H" FOR .125 BOARD 3.17	OVERALL LENGTH DIM "L"	CUSTOMER RESTRICTED			
	7615X-001	.230/5.84	.045/1.14	.039/0.99	NOTE 7	.235/5.97	.220/5.59	.205/5.21	.345/8.76	NO			
	7615X-002	.265/6.73	.045/1.14	.039/0.99	NOTE 7	.270/6.86	.255/6.48	.240/6.10	.380/9.65	NO			
	7615X-003	.345/8.76	.045/1.14	.039/0.99	NOTE 7	.350/8.89	.335/8.51	.320/8.13	.460/11,68	NO			
	7615X-004	.400/10.16	.045/1.14	.039/0.99	NOTE 7	.405/10.29	.390/9.91	.375/9.53	.515/13.08	NO			
	7615X-005	.415/10.54	.045/1.14	.039/0.99	NOTE 7	.420/10.67	.405/10.29	.390/9.91	.530/13.46	NO			
	7615X-006	.435/11.05	.045/1.14	.039/0.99	NOTE 7	.440/11.18	.425/10.80	.410/10.41	.550/13.97	NO			
	7615X-007	.465/11.81	.045/1.14	.039/0.99	NOTE 7	.470/11.94	.455/11.56	.440/11.18	.580/14.73	NO			
	7615X-008	.515/13.08	.045/1.14	.039/0.99	NOTE 7	.520/13.21	.505/12.83	.490/12.45	.630/16.00	NO			
	7615X-009	.575/14.61	.040/1.02	.039/0.99	NOTE 7	.575/14.61	.560/14.22	.545/13.84	.685/17.40	NO			
	7615X-010	.585/14.86	.045/1.14	.039/0.99	NOTE 7	.590/14.99	.575/14.61	.560/14.22	.700/17.78	NO			
	7615X-011	.635/16.13	.045/1.14	.039/0.99	NOTE 7	.640/16.26	.625/15.88	.610/15.49	.750/19.05	NO			
	7615X-012	.655/16.64	.045/1.14	.039/0.99	NOTE 7	.660/16.76	.645/16.38	.630/16.00	.770/19.56	NO			
	7615X-013	.745/18.92	.045/1.14	.039/0.99	NOTE 7	.750/19.05	.735/18.67	.720/18.29	.860/21.84	NO			
	7615X-014	.265/6.73	.245/6.22	.039/0.99	NOTE 7	.270/6.86	.255/6.48	.240/6.10	.580/14.73	NO			
	7615X-015	.345/8.76	.245/6.22	.039/0.99	NOTE 7	.350/8.89	.335/8.51	.320/8.13	.660/16.76	NO			A
Α	7615X-016	.400/10.16	.245/6.22	.039/0.99	NOTE 7	.405/10.29	.390/9.91	.375/9.53	.715/18.16	NO			
	7615X-017	.465/11.81	.245/6.22	.039/0.99	NOTE 7	.470/11.94	.455/11.56	.440/11.18	.780/19.81	NO			
	7615X-018	.570/14.48	.245/6.22	.039/0.99	NOTE 7	.575/14.61	.560/14.22	.545/13.84	.885/22.48	NO			
	7615X-019	.625/15.88	.245/6.22	.039/0.99	NOTE 7	.630/16.00	.615/15.62	.600/15.24	.940/23.88	NO			
	7615X-020	.655/16.64	.245/6.22	.039/0.99	NOTE 7	.660/16.76	.645/16.38	.630/16.00	.970/24.64	NO			
	7615X-021	.265/6.73	.355/9.02	.039/0.99	NOTE 7	.270/6.86	.255/6.48	.240/6.10	.690/17.53	NO			
	7615X-022	.345/8.76	.355/9.02	.039/0.99	NOTE 7	.350/8.89	.335/8.51	.320/8.13	.770/19.56	NO			
	7615X-023	.400/10.16	.355/9.02	.039/0.99	NOTE 7	.405/10.29	.390/9.91	.375/9.53	.825/20.96	NO			
	7615X-024	.465/11.81	.355/9.02	.039/0.99	NOTE 7	.470/11.94	.455/11.56	.440/11.18	.890/22.61	NO			
	7615X-025	.570/14.48	.355/9.02	.039/0.99	NOTE 7	.575/14.61	.560/14.22	.545/13.84	.995/25.27	NO			
	7615X-026	.625/15.88	.355/9.02	.039/0.99	NOTE 7	.630/16.00	.615/15.62	.600/15.24	1.050/26.67	NO			
	7615X-027	.655/16.64	.355/9.02	.039/0.99	NOTE 7	.660/16.76	.645/16.38	.630/16.00	1.080/27.43	NO			
В								maf1. code SEE NOTI Itr ecn no dr AA Sheet revision index sheet	date tolerances angles or ±2*	tolerance ASME Y44.5	projection INCH/MM scale 1:1 FSJ	.039"[0.99] DIA. STAR	44
	form: A4mmXLc			1			2	•		3		4	4
							I						

PDM: Rev:AA STATUS: Released Printed: Sep 24, 2008

		Copyright FCI.									
	_			1 2	FClcor	nnect.com			3	4	_
	PRODUCT NO. NOTE 9	CONTACT AREA DIM "A".	TERMINATION AREA DIM "B"	DIM "C"	DIM "H" FOR .062 BOARD 1.57	DIM "H" FOR .093 BOARD 2.36	DIM "H" FOR .125 BOARD 3.17	OVERALL LENGTH DIM "L"	CUSTOMER RESTRICTED		
	7615X-028	.305/7.75	.035/0.89	.039/0.99 NOTE 7	.310/7.87	.295/7.49	.280/7.11	.410/10.41	NO		
	7615X-029	.755/19.18	.345/8.76	.039/0.99 NOTE 7	.760/19.30	.745/18.92	.730/18.54	1.170/29.72	NO		
	7615X-030	.710/18.03	.345/8.76	.039/0.99 NOTE 7	.715/18.16	.700/17.78	.685/17.40	1.125/28.58	NO		
	7615X-031	.545/13.84	.198/5.03	.039/0.99 NOTE 7	.550/13.97	.535/13.59	.520/13.21	.813/20.65	NO		
	7615X-032									OBSOLETE	
	7615X-033	.335/8.51	.375/9.53	.039/0.99 NOTE 7	.340/8.64	.325/8.26	.310/7.87	.780/19.81	NO		
	7615X-034	.535/13.59	.045/1.14	.039/0.99 NOTE 7	.540/13.72	.525/13.34	.510/12.95	.650/16.51	NO		
	7615X-035	.560/14.22	.260/6.60	.039/0.99 NOTE 7	.565/14.35	.550/13.97	.535/13.59	.890/22.61	NO		
	7615X-036	.510/12.95	.381/9.68	.039/0.99 NOTE 7	.515/13.08	.500/12.70	.485/12.32	.961/24.41	NO		
	7615X-037	.325/8.26	.101/2.57	.039/0.99 NOTE 7	.330/8.38	.315/8.00	.300/7.62	.496/12.60	NO		
	7615X-038	.595/15.11	.330/8.38	.039/0.99 NOTE 7	.600/15.24	.585/14.86	.570/14.48	.995/25.27	NO		
	7615X-039	.755/19.18	.065/1.65	.039/0.99 NOTE 7	.760/19.30	.745/18.92	.730/18.54	.890/22.61	NO		
	7615X-040	.315/8.00	.395/10.03	.039/0.99 NOTE 7	.320/8.13	.305/7.75	.290/7.37	.780/19.81	NO		
	7615X-041	.230/5.84	.080/2.03	.039/0.99 NOTE 7	.235/5.97	.220/5.59	.205/5.21	.380/9.65	NO		
	7615X-042	.870/22.10	.045/1.14	.039/0.99 NOTE 7	.875/22.23	.860/21.84	.845/21.46	.985/25.02	NO		A
Α	7615X-043	.504/12.80	.329/8.36	.039/0.99 NOTE 7	.509/12.80	.494/12.55	.479/12.17	.900/22.86	NO		^
	7615X-044	.324/8.23	.056/1.42	.039/0.99 NOTE 7	.329/8.36	.314/7.98	.299/7.60	.450/11.43	NO		
	7615X-045	.499/12.68	.056/1.42	.039/0.99 NOTE 7	.504/12.80	.489/12.42	.474/12.04	.625/15.88	NO		
	7615X-046	.430/10.92	.535/13.59	.039/0.99 NOTE 7	.435/11.05	.420/10.67	.405/10.29	1.035/26.29	NO		
	7615X-047	.375/9.53	.070/1.78	.039/0.99 NOTE 7	.380/9.65	.365/9.27	.350/8.89	.515/13.08	NO		
	7615X-048	.375/9.53	.275/6.99	.039/0.99 NOTE 7	.380/9.65	.365/9.27	.350/8.89	.720/18.29	NO		
	7615X-049	.545/13.84	.070/1.78	.039/0.99 NOTE 7	.550/13.97	.535/13.59	.520/13.21	.685/17.40	NO		
	7615X-050	.313/7.95	.317/8.05	.039/0.99 NOTE 7	.318/8.08	.303/7.70	.288/7.32	.700/17.78	NO		
	7615X-051	.320/8.13	.045/1.14	.039/0.99 NOTE 7	.325/8.26	.310/7.87	.295/7.49	.435/11.05	NO		
	7615X-052	.620/15.75	.590/14.99	.039/0.99 NOTE 7	.625/15.88	.610/15.49	.595/15.11	1.280/35.51	NO		
	7615X-053	.245/6.22	.045/1.14	.039/0.99 NOTE 7	.250/6.35	.235/5.97	.220/5.59	.360/9.14	NO		
	7615X-054	.623/15.82	.270/6.86	.039/0.99 NOTE 7	.628/15.95	.613/15.57	.598/15.19	.963/24.46	NO		
В							mat'l. code SEE NOTE Itr ecn no dr c AA Sheet revision index sheet	date toterances ur angles 7 0° ±2° 9 dr M. engr L chr L	tolerance ASME Y14.5 lless otherwise specified XX*01/X*3 .XXX*005/XX*13 .XXXX*0020/XXX*051 FETROW 1994-05-16 .FYE 1994-05-16 .FYE 1994-05-16	projection PIN PRODUCTS title BERGPIN® LOOSE PIECE .039"[0.99] DIA. STAR dwg no sheet 4 of 5 size 76151 A2 type CUSTOMER Drawing	4
	form: A4mmXLc			1		2			3	4	

PDM: Rev:AA STATUS: Released Printed: Sep 24, 2008

Copyright FC1.

1 | 2

1

FClconnect.com

3 |

PRODUCT NO. NOTE 9	CONTACT AREA DIM "A"	TERMINATION AREA DIM "B"	DIM "C"	DIM "H" FOR .062 BOARD 1.57	DIM "H" FOR .093 BOARD 2.36	DIM "H" FOR .125 BOARD 3.17	OVERALL LENGTH DIM "L"	CUSTOMER RESTRICTED
7615X-055	.684/17.37	.051/1.30	.039/0.99 NOTE 7	.689/17.50	.674/17.12	.659/16.74	.800/20.32	NO
7615X-056	.295/7.49	.192/4.88	.039/0.99 NOTE 7	.300/7.62	.285/7.24	.270/6.86	.552/14.02	NO
7615X-057	.785/19.94	.050/1.27	.039/0.99 NOTE 7	.790/20.07	.775/19.69	.760/19.30	.900/22.86	NO
7615X-058	.747/18.97	.524/13.31	.039/0.99 NOTE 7	.752/19.10	.737/18.72	.722/18.34	1.335/33.91	NO
7615X-059	.230/5.84	.135/3.43	.039/0.99 NOTE 7	.235/5.97	.220/5.59	.205/5.20	.430/10.92	NO
7615X-060	.400/10.16	.440/11.18	.039/0.99 NOTE 7	.405/10.29	.390/9.91	.375/9.53	.910/23.11	NO
7615X-061	.280/7.11	.192/4.88	.039/0.99 NOTE 7	.285/7.24	.270/6.86	.255/6.48	.542/13.77	NO
7615X-062	.280/7.11	.085/2.16	.039/0.99 NOTE 7	.285/7.24	.270/6.86	.255/6.48	.435/11.05	NO
7615X-063	.100/2.54	.050/1.27	.039/0.99 NOTE 7	.105/2.67	.090/2.29	.075/1.91	.220/5.59	NO
7615X-064	.380/9.65	.650/16.51	.039/0.99 NOTE 7	.385/9.78	.370/9.40	.355/9.02	1.100/27.94	NO
7615X-065	.610/15.49	.030/0.76	.038/0.97 NOTE 8	.615/15.62	.600/15.24	.585/14.86	.710/18.03	YES
7615X-066	.822/20.88	.045/1.14	.039/0.99 NOTE 7	.827/21.01	.812/20.63	.797/20.24	.937/23.80	NO
7615X-067	.945/24.00	.045/1.14	.039/0.99 NOTE 7	.945/24.00	.935/23.75	.920/23.37	1.055/26.80	NO
7615X-068	.194/4.93	.042/1.07	.039/0.99 NOTE 7	.196/4.98	.181/4.60	.165/4.19	.306/7.77	NO
7615X-069	.220/5.59	.220/5.59	.039/0.99 NOTE 7	.225/5.72	.210/5.33	.195/4.95	.510/12.95	NO

mat'l. code product family
PIN PRODUCTS surface tolerance projection SEE NOTE 1 ASME Y14.5 ecn no dr date tolerances unless otherwise specified .XX±.01/.X±.3 BERGPIN® LOOSE PIECE .XXX±.005/.XX±.13 .039"[0.99] DIA. STAR .XXXX±.0020/.XXX±.051 sheet 5 of 5 size M. FETROW 1994-05-16 FCJ 1994-05-16 76151 1994-05-16 CUSTOMER Drawing appd 1994-05-19 sheet revision index

R

form: A4mmXLc

2

PDM: Rev:AA

STATUS: Released

Printed: Sep 24, 2008