

Printed: Jun 04, 2008

CATALOGUE RANGE

PLATING	PIN STYLE	MATING	SOLDER	
1/4/8	03	5.84	2.54	
1/4/8	04	5.84	3.05	
1/4/8	12	6.8	3.05	

PLATING
1 = 0.76µm GOLD/GXT ON CONTACT AREA
3.81µm TIN-LEAD ON TAIL
4 = 3.81µm TIN-LEAD ON CONTACT AREA
AND ON TAIL
8 = 0.38µm GOLD/GXT ON CONTACT AREA
3.81µm TIN-LEAD ON TAIL

- WHEN "LF" IS REQUIRED, 2µm MATTE
TIN OVER 1.27µm MIN NICKEL IS
PROVIDED INSTEAD OF TIN-LEAD

APPLICATION SPECIFIC

PLATING	PIN STYLE	MATING	SOLDER	
1/4/8	01	5.72	2.57	
1/4/8	14	10	2.7	
1/4/8	15	7	16.4	
1/4/8	16	7.8	13.5	
1/4/8	17	7.48	1.6	
1/4/8	18	8.80	2.90	

PLATING
1 = 0.76µm GOLD/GXT ON CONTACT AREA
3.81µm TIN-LEAD ON TAIL
4 = 3.81µm TIN-LEAD ON CONTACT AREA
AND ON TAIL
8 = 0.38µm GOLD/GXT ON CONTACT AREA
3.81µm TIN-LEAD ON TAIL

- WHEN "LF" IS REQUIRED, 2µm MATTE
TIN OVER 1.27µm MIN NICKEL IS
PROVIDED INSTEAD OF TIN-LEAD

mat'l. code				surface		tolerance		projection		product family	
SEE NOTES				ISO 1302		ISO 406 ISO 1101				BERGSTIK	
ltr	ecn no	dr	date	tolerances unless		otherwise specified				title	
X	F04-0362	LMU	04.11.29	angles	linear	.X ±0.3		scale 5:1		UNSHR.HEADER RA DR TMT	
AA	F06-0207	LMU	06.07.27			.XX ±.015					
AB	F06-0263	LMU	06.10.27			.XXX ±0.05					
AC	F08-0148	RTR	08.03.31	dr	D.LE	01.01.24				dwg no	
				enr	JM.C	01.01.24				sheet 2 of	
				chr	JM.C	01.01.24				77317	
				appd	JF.N	01.01.24				A3	
sheet index		revision sheet								type CUSTOMER Drawing	

form: A3

PDM: Rev:AE STATUS:Released Printed: Jun 04, 2008