




PRODUCT NUMBER	QUANTITY PER REEL	PACKAGING
77747-Y01(LF)	15000	CARDBOARD REEL
77747-Y11(LF)	3000	CARDBOARD REEL

WHEN NEEDED, SUFFIX LETTER "LF" INDICATES THE PRODUCT IS RoHS COMPATIBLE, SEE NOTE 3



REELING AFTER STAMPING

- NOTES:
- 1 – MATERIAL: PHOSPHOR BRONZE, EXTRA HARD
 - 2 – FOR APPLICATION DATA, SEE TA 338
 - 3 – RoHS COMPATIBLE PRODUCT SPECIFICATIONS
 - a – PLATING:
 - "LF" MEANS THE PRODUCT IS LEAD-FREE, 2µm MINIMUM MATTE TIN OVER 1.27µm MINIMUM NICKEL UNDERPLATE.
 - b – LABELING:
 - MEETS PACKAGING SPECS AS PER GS-14-920
 - c – LEGAL STATEMENT: SEE GS-22-008
- THE PRODUCT IS NOT INTENDED TO BE EXPOSED TO A MANUFACTURING SOLDER PROCESS.

77747-3XXLF	0.76μm Au	Sn	0.3 N MIN
			0.6 N MAX
77747-4XXLF	5μm Sn	Sn	0.3 N MIN
			0.6 N MAX
77747-3XX	0.76μm Au	SnPb	0.3 N MIN
			0.6 N MAX
77747-4XX	5μm SnPb	SnPb	0.3 N MIN
			0.6 N MAX
PLATING CODE	CONTACT AREA	SOLDER TAIL	WITHDRAWAL FORCE USING SQUARE PIN 0.61
	PLATING THICKNESS OVER 1.27 Ni MIN		

mat'L code SEE NOTES				surface ISO 1902	tolerance ISO 416 ISO 1101	projection mm	product family DUFLEX			
Ltr	ecn	no	dr	date	tolerances unless otherwise specified		mm	title DUFLEX TERMINAL		
F	F05-0286	DLE	03.11.07		angles	linear				
a	F06-0203	DLE	06.06.21		±2°		scale 10:1	dwg no 77747 sheet 1 of 1 size A3		
H	F07-0271	LMU	07.11.14							
				dr	D LEGRAND	04.12.16	FCJ	type CUSTOMER Drawing		
				engr	P NIZZI	04.12.16				
				chr	P NIZZI	04.12.16				
				appd	P NZ	04.12.16				
sheet index	revision sheet									