

2 inch wide ESD Tape Dispenser

- **Use with Wescorp and other brand antistatic tapes**
Can be used with standard 3-inch core tapes.
- **Groundable Housing and Hardware**
Components of ESD tape dispenser can be grounded with ground cord (or through work surface*) to be used in ESD Protected Area
Included nut assembly can be used to secure ground cord to tape dispenser on either side, depending on needs.
- **Stainless Steel Construction**
Minimizes foreign objects debris, corrosion, and other contamination when used in clean or sensitive areas.
Simplifies cleaning.
- **Two Separate Spools Turn Independently**
Holds one 2-inch wide roll of tape or two rolls of tape that are 1-inch or less widths, depending on needs.
- **Heavy Weighted Design**
Extra weight allows for one-handed use; dispenser will not slide on most surfaces.
- **Grounding Jack**
For operator personnel grounding with wrist strap or other grounding requirements
- **Made in America**

*Best practice is grounding via supplied ground cord. Attach cord to snap on chassis and to common point ground. If grounded via placing on a grounded ESD worksurface, resistance to ground (RTG) should be periodically tested $<1 \times 10E9$ ohms.

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." [ESD Handbook ESD TR20.20 section 2.4 Sources of Static Electricity]

DESCO

ESD Tape Dispenser, 2"

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: www.desco.com
PHONE (909) 627-8178 FAX (909) 627-7449 FAX REQUEST (909) 627-7126

DESCO EAST: 90 HUDSON RD, CANTON, MA 02021-1407
PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER
81282

DATE:
August 2008

© 2008 DESCO INDUSTRIES INC.
Employee Owned