






NOTES:

- 1-Material:phosphor bronze,thickness 0.20
- 2-Finish on contact area:see table
finish on termination:bright tin lead over nickel
- 3-Wire range:24 to 28 AWG
- 4-Max outer dia of wire insulator:1.02 mm
- 5-Current carrying capacity per contact:
 - 3.Amps max when crimped to #24 AWG
 - 2 Amps max when crimped to #26 AWG
 - 1 Amps max when crimped to #28 AWG
- 6-After 5 insertions into connector,
contact retention must be 5 pounds axial load min
- 7-When contact is crimped to 24 AWG,the insulation
support crimped height must be 1.78 mm max to ensure
a proper insertion into housing
- 6-Packaging:BOX of 500 contacts

NOTE : ROHS INFORMATION

The LF products meet European union directives and other
country regulations as described in GS-22-008
Terminations plating spec : 2um Nickel min + 2um Sn min
Packaging Spec : see GS-14-920

CORE RANGE	
8656351067LF	0.4μ Au
8656351067	0.4μ Au
8656351065LF	0.76μ Au
8656351065	0.76μ Au
8656351066LF	1.25 Au
8656351066	1.25μ Au
PART NUMBER	Plating



www.fciconnect.com		surface - ISO 1302	tolerance std ISO 406 ISO 1101	projection mm
		TOLERANCES UNLESS OTHERWISE SPECIFIED		size A3
Dr	C JARRY	28/01/97	ANGULAR	0.X ±0.3
Eng			LINEAR	0.XX ±0.1
Chr			0° ±2°	0.XXX ±0.05
Appr			Product family	ECN LS08-0127
				Spec ref
FCI		CRIMP SOCKET		Rev. D
		# Wire 20-24 Ø1.52 MAX		
		catalog no		
		CUSTOMER		sheet 1 of 1

rev	ecn no	dr	date
B	LS05-006	MPE	25-06-05
C	LS06-0196	MPE	27/11/2006
D	LS08-0127	MPE	2008/05/13
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

REV F - 2006-04-17