


REFERENCE FOR REEL ACCORDING TO FEEDING DIRECTION

GAUGE	REEL OF 5000 FEMALE CTS		REEL OF 10 000 FEMALE CTS		GAUGE	REEL OF 5000 PIN CONTACTS		REEL OF 10 000 PIN CTS	
# 24-28	86566510064	86566510064LF		-	# 24-28	86564510064	86564510064LF		-
# 20-24	86566520064	86566520064LF	86566530064	86566530064LF	# 20-24	86564520064	86564520064LF	86564530064	86564530064LF

$\varnothing$ 450 mm reel of 5000
 $\varnothing$ 600 mm reel of 10 000

SEE DETAIL B


DETAIL B
 SCALE 3.000



Manufacturer's code

SEE DETAIL A

DETAIL A
 SCALE 3.000



Manufacturer's code

CONTACT DIMENSIONS
 SEE SHEET 2/2

CORE RANGE

NOTE: ROHS INFORMATIONS
 The LF products meet European union directives and other country regulations as described in GS-22-008
 Terminations plating spec: 2µm Nickel min + 2µm Sn min
 Packaging spec: see GS-14-920

rev	ecn no	dr	date
F	LS06-196	MPE	27/11/2006
G	LS08-0127	MPE	2008/05/13
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com		surface -	tolerance std	projection	mm
		ISO 1302	ISO 406 ISO 1101		
		TOLERANCES UNLESS OTHERWISE SPECIFIED			
Dr	-	18/04/03	ANGULAR	size A3	Scale 1.000
Eng	-	-	LINEAR		
Chr	-	-	0° ±2°		
Appr	-	-	0.X ±0.3		
			0.XX ±0.1		
			0.XXX ±0.05		
		Product family	-	ECN	LS08-0127
				Spec ref	-
FCI		CRIMP PIN	dwg no	C01-8656-0522	
		#Wire 24-28 01.02			
		catalog no	-	customer	sheet 1 of 2

REV F - 2006-04-17

