



- NOTES:
1. RECOMMENDED P.C.B. THICKNESS 1.60 MM.
 2. HOUSING MATERIAL: ZYTEL FR50, COLOR: SEE TABLE.
 3. CONTACTS: PHOS BRONZE ALLOY UNS-C51000, 0.460 DIA. ROUND WIRE. PLATING SEE TABLE.
 4. PACKAGE PER BUS-14-164. (TUBE PACKAGING) WHEN PART NUMBER IS 88400-XXXT/-XXXTLF, APPLY PACKAGING SPEC. GES-14-351 (TRAY PACKAGING).
 5. THE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
 6. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.60mm MINIMUM THICK CIRCUIT BOARD.
 7. IF LF P/N PACKAGING MEETS GS-14-920 SPECIFICATION.

mat'l code					tolerance unless otherwise specified			CUSTOMER COPY				www.fciconnect.com	
rev.	ecn no.	dr	date		linear	.0 ± 0.25			projection 	title SNAP-IN MODULAR JACK ASS'Y			
K	T90139	M W	04/06/99			.00 ± 0.13							
L	N05-0019	YS	01/27/05			.000± 0.05							
					angles	± 2°							
					dr	KCHOU	04/26/92	unit	product family		code		
					enr	TONY CHIEN	04/26/92	mm/inch	size		dwg no.		
					chr	TONY CHIEN	04/26/92	scale	A3		78400		
					appd	JENN TSAO	04/26/92	2/1			sheet 1 OF 2		
sheet index	revision sheet	L 1	L 2										



PLATING & HSG COLOR CODE	PLATING	HSG COLOR
0	30 v " G.X.T.	BLACK
1	15 v " GOLD.	
2	20v " GFPD.	
3	30 v " GOLD.	
4	15 v " G.X.T.	
5	50 v " GOLD.	
6	6 v " GOLD.	
7	2 v " GOLD.	

