


DATA SHEET

Product Number: 940-44-032-17-400000



FOR PRINTED CIRCUIT DRILLING PATTERNS

SEE APPLICATION NOTES () ABOVE

Description:

PLCC Socket
Standard
Non-Lubricated
Surface Mount

Plating Code:

44

Shell Plating:

200 μ " Tin (matte finish) over 100 μ " Nickel

Inner Contact Plating:


100 μ " Tin (matte finish) over 50 μ " Nickel

Packaging:

Packaged in Tubes

Note: PLCC Sockets with "99" (tin/lead) plating code are being discontinued and will only be available in RoHS compliant "44" (pure tin).

"99" plating is still available in limited quantities until all existing stock is depleted.

# Of Pins	A	B	C	Qty. per Tube	Mill-Max Part Number	RoHS Compliant
32	.813/.713 Rectangle	.400/.300 Rectangle	.534/.434 Rectangle	24	940-44-032-17-400000	

INSULATOR INFORMATION:

PPS (Ryton R-4-200)

High Temperature

Properties of PPS:

- Brand: Ryton
- Grade: R-4-200
- Material Heat Deflection Temp. (per ASTM D 648): >500°F (>260°C) @ 264 psi

Note: Materials above 446°F (230°C) are considered suitable for "eutectic" reflow soldering, above 500°F (260°C) for "lead-free" reflow soldering.