









PRODUCT N°
SEE TABLE



rev	ecn no	dr	date
M	F06-0152	DLE	06.03.20
N	F06-0242	DLE	06.07.20
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com			surface -  ISO 1302		tolerance std ±0.13 ±2°		projection 		mm 		
			TOLERANCES UNLESS OTHERWISE SPECIFIED								
Dr	D LEGRAND	02.09.16	ANGULAR	LINEAR	D.X ±Y		size A3	Scale 3:1			
Eng	P NIZZI	02.09.16			O.XX ±Y						
Chr	D LEGRAND	02.09.16			a.XXX ±Y						
Appr	P NIZZI	02.09.16	a° ±Y°				ECN F06-0242				
			Product family MODULAR JACK					Spec ref -			
			title VERTICAL SMT				dwg no 98433			Rev. N	
			6 POSITIONS KEYED								
			catalog no 98433-XXX(LF)				CUSTOMER			sheet 1 of 2	

PRODUCT N°
98433-XXXLF

CONTACT PLATING
OPTION

1= GXT 0 76 μm
3= 0.76 μm GOLD
5= 1.27 μm GOLD

PACKAGE OPTIONS

TAPE AND REEL PACKAGE
1= LOADED FACE UP
TAPE AND REEL PACKAGE
2= LOADED FACE DOWN

VERSION

TOP (RED)
BOTTOM (RED)




TERMINAL LOADING
OPTIONS

1= FULLY LOADED
6 POSITIONS
2= ONLY POS 2,3,4,5
LOADED
3= ONLY POS 1,2,5,6
LOADED





WHEN NEEDED, SUFFIX LETTER "LF"
INDICATES THE PRODUCT IS RoHS
COMPATIBLE SEE NOTE 7.

NOTES:

- 1 - MATERIAL:
HOUSING: HIGH TEMP. PLASTIC, COLOR RED
TERMINAL PHOSPHOR BRONZE
- 2 - PLATING
CONTACT AREA: OPTIONAL SEE TABLE
SOLDER TAIL: SnPb 90/10 2 μm MIN
NO RAW EDGES EXCEPT SOLDER TAILS TIPS
- 3 - AREA FOR VACUUM PICK AND PLACE VENTURY
- 4 - PACKAGING SPECIFICATION SEE TA 858
- 5 - DIMENSION MEASURED FROM "A" TO THE TOP OF PRODUCT
- 6 - COPLANARITY SEE TA 861.
- 7 - RoHS COMPATIBLE PRODUCT SPECIFICATIONS
- a - PLATING:
 - "LF" MEANS THE PRODUCT IS LEAD-FREE,
2 μm MINIMUM MATTE TIN OVER 1.27 μm
MINIMUM NICKEL UNDERPLATE.
- b - MANUFACTURING PROCESS COMPATIBILITY:
 - THE HOUSING WILL WITHSTAND EXPOSURE TO
245 °C PEAK TEMPERATURE FOR 30 SECONDS
MAX IN A CONVECTION, INFRA-RED OR VAPOR
PHASE OR REFLOW OVEN.
- c - LABELLING:
 - MEETS PACKAGING SPECS AS PER GS-14-920.
- d - LEGAL STATEMENT: SEE GS-22-008



RECOMMENDED PCB FOOTPRINT

www.fciconnect.com			surface - 		tolerance std ISO 1302 ±0.13 ±2°		projection 		mm 		
			TOLERANCES UNLESS OTHERWISE SPECIFIED								
Dr	D LEGRAND	02.09.16	ANGULAR	LINEAR	D.X ±Y		size A3	Scale 5:1			
Eng	P NIZZI	02.09.16			0.XX ±Y						
Chr	D LEGRAND	02.09.16			0.XXX ±Y						
Appr	P NIZZI	02.09.16	0° ±Y°	Product family MODULAR JACK				ECN F06-0242 Spec ref -			
			title VERTICAL SMT 6 POSITIONS KEYED				dwg no 98433			Rev N	
			catalog no 98433-XXX(LF)				CUSTOMER		sheet 2 of 2		