


SPECIFICATIONS

	REVISIONS		
LTR	DESCRIPTION	DATE	APPROVED
_	RELEASED FROM ENGINEERING	3/11/05	

PARAMETERS	VALUES	UNITS
RATED INPUT POWER	2	W
MAX INPUT POWER	4	W
IMPEDANCE	8±15%	ОНМ
OUTPUT SPL @ 1W/1M (AT 0.6, .8, 1.0, 1.2 1.5 kHz)	86±3	dBA
DISTORTION (MAX.)	7%	ı
RESONANT FREQUENCY	300±20%	Hz
FREQUENCY RANGE	300 ~ 20,000	Hz
HOUSING MATERIAL	METAL	ı
CONE MATERIAL	PAPER	-
MAGNET MATERIAL	FERRITE	-
OPERATING TEMPERATURE	−25 ~ +55	ပဲ
WEIGHT	143	grams

 70 ± 0.5 ϕ 74 ± 0.5 ϕ 76.3



NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.

FILE NAME AS07008PS—R.DWG

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS, TOLERANCES AR ANGLES ARE ±3'.		i
ANGES ARE 10.		
APPROVALS	DATE	

APPROVALS		DATE	
DRAWN	J.D.	9/06	
CHECKED	B.R.	9/06	
APPROVED	R.W.	9/06	
DO NOT SCALE DRAWING			

projects ® unlimited

Dayton , Ohio

SPEAKER

A ASO7008PS-R

SCALE: N.T.S. SHEET 1 OF 1