

Ordering code system


B37830


R


0


101


K


0


2


1

Packaging
 1 $\triangleq$ cardboard tape, 180-mm reel
 3 $\triangleq$ cardboard tape, 330-mm reel

2 $\triangleq$ 2-fold array
4 $\triangleq$ 4-fold array

Internal coding: 0 or decimal place for cap. values < 10 pF

Capacitance tolerance

 J $\triangleq \pm 5\%$
K $\triangleq \pm 10\%$ (standard for C0G)
M $\triangleq \pm 20\%$ (standard for X7R)

Capacitance, coded $100 \triangleq 10 \cdot 10^0 \text{ pF} = 10 \text{ pF}$
 (example) $101 \triangleq 10 \cdot 10^1 \text{ pF} = 100 \text{ pF}$
 $220 \triangleq 22 \cdot 10^0 \text{ pF} = 22 \text{ pF}$

Rated voltage	Rated voltage [VDC]	16	25	50
	Code	9	0	5

Termination Standard: R $\triangleq$ nickel barrier for all case sizes
 "R" also indicates array capacitor

Type and size

Chip size (inch / mm)	Temperature characteristic		
	C0G	X7R	
0405 / 1012	B37830	B37831	
0508 / 1220	B37940	B37941	
0612 / 1632	B37871	B37872	

Features

- Reduction of mounting time and mounting costs
- Space saving on the PCB

Applications

- Suitable for electronic circuits with parallel line layout
- Coupling and filtering, particularly in RF circuits
- Resonant circuits
- Filter circuits

Termination

- For soldering: Nickel-barrier terminations (Ni)

Options

- Alternative capacitance tolerances available on request


Delivery mode

- Cardboard tape, 180-mm and 330-mm reel available

Electrical data

Temperature characteristic		C0G	
Climatic category (IEC 60068-1)		55/125/56	
Standard		EIA	
Dielectric		Class 1	
Rated voltage	V_R	25, 50	VDC
Test voltage	V_{test}	$2,5 \cdot V_R/5$ s	VDC
Capacitance range / E series	C_R	10 pF ... 1,0 nF (E6)	
Temperature coefficient		$0 \pm 30 \cdot 10^{-6}/K$	
Dissipation factor (limit value)	$\tan \delta$	$< 1,0 \cdot 10^{-3}$	
Insulation resistance ¹⁾ at + 25 °C	R_{ins}	$> 10^5$	MΩ
Insulation resistance ¹⁾ at +125 °C	R_{ins}	$> 10^4$	MΩ
Time constant ¹⁾ at + 25 °C	τ	> 1000	s
Time constant ¹⁾ at +125 °C	τ	> 100	s
Operating temperature range	T_{op}	-55 ... +125	°C
Ageing		none	

1) For $C_R > 10$ nF the time constant $\tau = C \cdot R_{ins}$ is given.




Capacitance tolerances


Code letter	J	K (standard)
Tolerance	$\pm 5\%$	$\pm 10\%$

Dimensional drawing

2-fold array (case size 0405)




4-fold array (case sizes 0508 and 0612)



Dimensions (mm)


Case size (inch) (mm)	2-fold array	4-fold array	
	0405 1012	0508 1220	0612 1632
<i>l</i>	$1,37 \pm 0,15$	$2,0 \pm 0,2$	$3,2 \pm 0,2$
<i>b</i>	$1,0 +0/-0,15$	$1,25 \pm 0,15$	$1,6 \pm 0,2$
<i>s</i>	0,70 max.	$0,85 \pm 0,1$	$0,85 \pm 0,1$
<i>k</i>	$0,36 \pm 0,1$	$0,3 \pm 0,1$	$0,4 \pm 0,15$
<i>e</i>	0,64	$0,5 \pm 0,1$	$0,8 \pm 0,15$
<i>u</i>	$0,2 \pm 0,1$	$0,2 +0,3/-0,1$	$0,2 +0,3/-0,1$

Tolerances to CECC 32101-801




Recommended solder pad

2-fold array (case size 0405)




4-fold array (case sizes 0508 and 0612)




Maximum dimensions (mm)

Case size	(inch/mm)	Type	A	B	C	D	P
0405/1012		2-fold array	0,55	0,28	1,38	0,40	0,64
0508/1220		4-fold array	0,90	0,40	2,20	0,35	0,50
0612/1632		4-fold array	1,00	1,10	3,10	0,45	0,90

Termination






Product range array capacitors

	C0G					
	2-fold arrays		4-fold arrays			
Size ¹⁾ inch mm	0405 1012		0508 1220		0612 1632	
Type	B37830		B37940		B37871	
V_R (VDC)	25		50		50	
C_R						
10 pF						
15 pF						
22 pF						
33 pF						
47 pF						
68 pF						
100 pF						
150 pF						
180 pF						
220 pF						
330 pF						
470 pF						
680 pF						
1,0 nF						

¹⁾ $l \times b$ (inch) / $l \times b$ (mm)



Multilayer Ceramic Capacitors

C0G; 0405

Ordering codes and packing for C0G arrays, 25 VDC, nickel-barrier terminations


$C_R^{1)}$	Ordering code ²⁾	Chip thickness	Cardboard tape, Ø 180-mm reel	Cardboard tape, Ø 330-mm reel
		mm	* $\triangleq$ 1	* $\triangleq$ 3
			pcs/reel	pcs/reel

Case size 0405, 25 VDC, 2-fold arrays

10	pF	B37830R0100K02*	0,6 $\pm$ 0,1	5000	20000
15	pF	B37830R0150K02*	0,6 $\pm$ 0,1	5000	20000
22	pF	B37830R0220K02*	0,6 $\pm$ 0,1	5000	20000
33	pF	B37830R0330K02*	0,6 $\pm$ 0,1	5000	20000
47	pF	B37830R0470K02*	0,6 $\pm$ 0,1	5000	20000
68	pF	B37830R0680K02*	0,6 $\pm$ 0,1	5000	20000
100	pF	B37830R0101K02*	0,6 $\pm$ 0,1	5000	20000
150	pF	B37830R0151K02*	0,6 $\pm$ 0,1	5000	20000
180	pF	B37830R0181K02*	0,6 $\pm$ 0,1	5000	20000

1) Other capacitance values on request.

2) The table contains the ordering codes for the standard capacitance tolerance.
For other available capacitance tolerances see page 94.


Ordering codes and packing for C0G arrays, 50 VDC, nickel-barrier terminations

$C_R^{1)}$	Ordering code ²⁾	Chip thickness	Cardboard tape, Ø 180-mm reel	Cardboard tape, Ø 330-mm reel
		mm	* $\triangleq$ 1	* $\triangleq$ 3
			pcs/reel	pcs/reel

Case size 0508, 50 VDC, 4-fold arrays


10	pF	B37940R5100K04*	0,85 $\pm$ 0,1	4000	16000
15	pF	B37940R5150K04*	0,85 $\pm$ 0,1	4000	16000
22	pF	B37940R5220K04*	0,85 $\pm$ 0,1	4000	16000
33	pF	B37940R5330K04*	0,85 $\pm$ 0,1	4000	16000
47	pF	B37940R5470K04*	0,85 $\pm$ 0,1	4000	16000
68	pF	B37940R5680K04*	0,85 $\pm$ 0,1	4000	16000
100	pF	B37940R5101K04*	0,85 $\pm$ 0,1	4000	16000
150	pF	B37940R5151K04*	0,85 $\pm$ 0,1	4000	16000
220	pF	B37940R5221K04*	0,85 $\pm$ 0,1	4000	16000

Case size 0612, 50 VDC, 4-fold arrays

10	pF	B37871R5100K04*	0,85 $\pm$ 0,1	4000	16000
15	pF	B37871R5150K04*	0,85 $\pm$ 0,1	4000	16000
22	pF	B37871R5220K04*	0,85 $\pm$ 0,1	4000	16000
33	pF	B37871R5330K04*	0,85 $\pm$ 0,1	4000	16000
47	pF	B37871R5470K04*	0,85 $\pm$ 0,1	4000	16000
68	pF	B37871R5680K04*	0,85 $\pm$ 0,1	4000	16000
100	pF	B37871R5101K04*	0,85 $\pm$ 0,1	4000	16000
150	pF	B37871R5151K04*	0,85 $\pm$ 0,1	4000	16000
220	pF	B37871R5221K04*	0,85 $\pm$ 0,1	4000	16000
330	pF	B37871R5331K04*	0,85 $\pm$ 0,1	4000	16000
470	pF	B37871R5471K04*	0,85 $\pm$ 0,1	4000	16000
680	pF	B37871R5681K04*	0,85 $\pm$ 0,1	4000	16000
1,0	nF	B37871R5102K04*	0,85 $\pm$ 0,1	4000	16000


1) Other capacitance values on request.

2) The table contains the ordering codes for the standard capacitance tolerance.
For other available capacitance tolerances see page 94.




Typical characteristics


Capacitance change $\Delta C/C_{25}$ versus temperature T (tolerance range $\pm 0.1\%$)




Capacitance change $\Delta C/C_0$ versus superimposed DC voltage V




Impedance $|Z|$ versus frequency f




Dissipation factor $\tan \delta$ versus temperature T






Typical characteristics

Insulation resistance R_{ins} versus temperature T



Capacitance change $\Delta C/C_1$ versus time t



Herausgegeben von EPCOS AG**Unternehmenskommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND****☎ ++49 89 636 09, FAX (0 89) 636-2 26 89**

© EPCOS AG 2002. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

Published by EPCOS AG**Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY****☎ ++49 89 636 09, FAX (0 89) 636-2 26 89**

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.