

JKL LAMP PART NO.	COLOR WHITE 6900°KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) (AVG.)	
BF20125-28B	x = .325 y = .295	700 @ 0°C	280	5	38,000 TYP.	20,000	

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC	IN MILLIMETERS		COMPONENTS COPPODATION						TON
	 	-	THIRD ANGLE	OTHERWIS 1 PL - 2 PL -	NCE UNLESS BE SPECIFIED +/- 0.2 +/- 0	TITLE	MIN		COL	O CATHODE	ORAI	1011
			PROJECTION DRAWN BY L. WENGSTROM	ANGLE - APPV'D B'	•	SIZE	FSCM NO. 55335	DRAWING		20125-28B		
REV.	RELEASE & CANCEL P-0404-14 DESCRIPTION/ECO NUMBER	4/22/04 APPV'D DATE			SCALE		RELEASED	2/04	REVISION DATE	REV. NO.	SHEET 1 OF 1	