



JKL LAMP PART NO. (REF.)	COLOR WHITE 4200°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF20137-26B	x = .372 y = .371	1125 @ 0°C	320	5	42,000 ± 15%	10,000 MIN.

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b>  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>							
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP									
			DRAWN BY L. WENGSTROM		APPV'D BY J.K.		DATE 2/23/05		SIZE <b>A</b>		FSCM NO. <b>55335</b>	DRAWING NO. <b>BF20137-26B</b>		
RELEASE AND CANCEL P-0310-09			2/23/05		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 2/23/05		REVISION DATE		REV. NO.	SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER			APPV'D DATE										