


JKL PART NUMBER	-A- LENGTH	LCD HIGH OUTPUT WHITE RGB COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF2661-24B	61±1.0**	9,400°k x = .285 ± .03 y = .290 ± .03	490 @ 0°C	195	5 ± 1	30,000 TYP.	35,000 AVG.
BF26180-24B	180±3.0		975 @ 0°C	390			
BF26188-24B	188±3.0		1115 @ 0°C	405			
BF26214-24B	214±2.0		1150 @ 0°C	460			
BF26230-24B	230±3.0		1240 @ 0°C	495			
BF26240-24B	240±3.0		1290 @ 0°C	515			
BF26250-24B	250±1.5		1350 @ 0°C	540			

NOTES:

* RATED LIFE IS DEFINED AS THE POINT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

** LEAD LENGTH 15±3.0.

RATINGS AT 25°C UNLESS OTHERWISE SPECIFIED.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0		JKL COMPONENTS CORPORATION TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP					
C	CORRECT x & y TOLERANCE	7/5/06	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING NO.				
B	LENGTH TOLERANCE CHANGE ON BF26250-24B	2/3/06	L. WENGSTROM	L.R.	7/5/06	A	55335	BF 26-24B				
A	ELECTRICAL CHANGES & ADD PART BF2661-24B	10/20/04										
	RELEASED TO CAD MULTI LIST	8/14/03										
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE		RELEASED DATE	REVISION DATE	REV. NO.	SHEET	
						NONE		8/14/03	7/5/06	C	1 OF 1	