


JKL PART NUMBER	-A- LENGTH	LCD HIGH OUTPUT WHITE RGB COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF2698-20B	98±2.0	5,400°k x = .336 y = .353	690 @ 0°C	275	5 ± 1	30,000 TYP.	35,000 AVG.
BF26188-20B	188±3.0		1115 @ 0°C	405			
BF26214-20B	214±2.0		1150 @ 0°C	460			
BF26285-20B	285±1.5		1525 @ 0°C	610			
BF26318-20B	318±1.5		1710 @ 0°C	685			
BF26360-20B	360±1.5		1940 @ 0°C	775			

NOTES:

* RATED LIFE IS DEFINED AS THE POINT WHICH INTENSITY BECOMES 50% OF THE INITIAL RATING.

RATING AT 25°C UNLESS OTHERWISE SPECIFIED.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- REF.		JKL COMPONENTS CORPORATION											
							TITLE											
							MINIATURE COLD CATHODE FLUORESCENT LAMP											
C	BF26285-20B LENGTH TOLERANCE CHANGE		2/3/06		DRAWN BY L. WENGSTROM	APPV'D BY LEW	DATE 2/3/06	SIZE A	FSCM NO. 55335	DRAWING NO. BF 26-20B								
B	ADD PART BF2698-20B		2/1/04															
A	ELECTRICAL CHNG. & ADD BF26318 & BF26360		10/20/04															
	RELEASED TO CAD MULTI LIST		8/14/03															
REV. NO.	DESCRIPTION/ECO NUMBER		APPV'D DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED				SCALE NONE		RELEASED DATE 8/14/03		REVISION DATE 2/3/06		REV. NO. C		SHEET 1 OF 1	