






Date	SYM	REVISION RECORD	AUTH	DR.	CK.
6/09/07	A	REDRAWN DIM. 18.26 WAS 18.03	T.B.	B.S.	
12/01/07	B	REMOVED "SOLDER DIPPED PCB TAILS"	T.B.	B.S.	



SPECIFICATIONS:

HOLDER MATERIAL: SELF EXTINGUISHING THERMOPLASTIC,
BLACK PBT

FLAMABILITY RATING:UL94V-0, FILE #E53829

CONTACTS: 301 SPRING TEMPER STAINLESS STEEL, NICKLE
PLATED OVERALL

DIELECTRIC STRENGTH: 560 VOLTS/MIL AT 25°C FOR 5 SEC.

TEMPERATURE RANGE: -55°C TO +180°C

RESISTANCE TO SOLVENTS: XYLENE, ETHYL , BUTYL, MRTHYL,
PROPYL ALCOHOL, ETHYL ACETATE,
HEPTANE, TOLUENE, REFRIGERANT

NOTES:

EYELET STIMPSON STYLE#A1883 0.110" OD x 0.190" FLANGE
FLANGE RECESS $\phi 0.203$ " x 0.090" DEEP
ACCEPTS STANDARD 2-56 MACHINE SCREWS

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal $\pm .5$ (.020)	Scale		Drawn By B.S.
Fractional $\pm .8$ (.030)	Title		Approved By T.B.
Angular $\pm 3^\circ$	Date 12/01/07	Drawing Number BH2/3A	