

PCB LAYOUT

Date	SYM	REVISION RECORD	AUTH	DR.	CK.
10/01/05	A	Added contact details. Material thickness was 0.020"	T.B.	B.S.	
4/22/06	B	Added "ROHS COMPLIANT"	T.B.	B.S.	
1/11/08	C	Dim. .154 was .204 Dim. .028 was .025	T.B.	B.S.	


#55(ϕ .052) Drill 2PL

.787 [20.00]



(-)Neg Term.

(+)Pos Term.


ϕ 1.13[ϕ 28.80]



.02 [0.5]



SQUARE CONTACT DETAIL



SPECIFICATIONS

*Holder material- Black PBT

*Flammability rating-UL94V-0, UL file no. E53829

*Contacts :

Positive: 0.0236" thick PHOS-BRONZE, Nickel Pltd.

Negative: 0.0236" thick spring tempered Stainless Steel, Nickel Pltd.

*Temperature Range: -40°C to +140°C

ROHS COMPLIANT

Tolerance (Except as noted)	 Memory protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal $\pm$.5 (.020)	Scale		Drawn By B.S.
Fractional $\pm$.8 (.030)	Title BATTERY HOLDER		
Angular $\pm$ 3°	Date 1/11/08	Drawing Number BH2430T-C	
		Approved By T.B.	