

Date	SYM	REVISION RECORD	AUTH	DR.	CK.

#58(.042) Drill 2PL

(-)Negative Terminal

Round Pin

$\pm .015$

.393 (9.98) Square Contact

(+)Positive Terminal

$\phi .595$  [ $\phi 15.11$ ]

$\phi .374$  [ $\phi 9.50$ ]

$\phi .050$  [ $\phi 1.27$ ]

BH500

MPD

.148 [3.76]

.100 [2.53]


.180(4.57)

.454 [11.53]

.755 [19.17]

## SPECIFICATIONS

- \*Holder material-thermoplastic, black PBT
- \*Flammability rating-UL94V-0, File No.88499(M)
- \*Contacts-302 spring temper stainless steel nickel plated overall
- \*Dielectric strenth-560volts/mil at 25°C for 5seconds
- \*Temperature range- -55° to +180°C
- \*Resistance to solvents-Xylene,ethyl,butyl,methyl&proptl alcohol;ethyl acetate,heptane;toluene;refrigerant

Tolerance (Except as noted)	 <b>Memory protection Devices, Inc</b> 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal $\pm .5$ (.020)			Scale 4=1 Drawn By T.S. Approved By T.B.
Fractional $\pm .8$ (.030)	Title CR/BR 1216, 1220, 1225 BATTERY HOLDER		
Angular $\pm 3^{\circ}$	Date 10/18/00	Drawing Number BH500	