

CENTER CONTACT: BRASS, NICKEL PLATED

SLIDING CONTACTS: PHOS. BRONZE, NICKEL PLATED

SPRING: SW70C, ZINC PLATED

FUSE: 250V, 5 AMP, 3AG 6.35mm x 30mm (1/4" X 1 1/4")

RATED AT 18 HOURS, CONTINUOUS DUTY

10 AMP'S MAX WITH CORRECT FUSE.

SWITCH: RED LED, 10 AMPS - 125 VOLTS

OR 5 AMPS - 250 VOLTS

WIRE: 6' LONG, 18AWG, VW-1, SPT-1, 105°C, (+)VE WIRE WITH A WHITE LINE INSIDE, (-)VE WIRE WITH WHITE MARKING ON IT **ROHS COMPLIANT**

Tolerance	M	Memory Protection Devices, Inc			
(Except as noted)		ale, New York 11735			
decimal				Scale	Drawn By B.S.
±.5 (.020)					Approved By T.B.
Fractional	Title LIGHTED ROTARY CIGARETTE PLUG WITH				
± .8 (.030)	6' WIRE, 10AMP SWITCH AND 5AMP FUSE				
Angular	Date		Drawing Nu	ımber	
± 3°	10/22/05		BK-5072		