



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP24V33

BP24V33 - External Battery Pack for UPS System



Highlights

- Extends runtime of Tripp Lite UPS Systems with 24V DC external battery connection
- Provides daisy-chain capability
- Simple installation; stackable
- 2 year warranty

Description

Tripp Lite's BP24V33 external battery pack offers extended battery runtime when used in conjunction with Tripp Lite SmartPro UPS systems with a 24VDC external battery connection. Stackable form factor supports configuration with up to 2 battery packs stacked with the UPS on top. Rugged all metal battery enclosure safely houses UPS batteries and includes heavy gauge cabling with pre-installed DC connectors for simple installation. Additional output connector allows multiple BP24V33 battery packs to be daisy-chained to the UPS for even longer extended run operation.

Applications

BP24V33 external battery pack is ideal for lengthening the battery runtime provided by Tripp Lite UPS systems equipped with a 24V DC external battery connection. Additional battery packs may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired. COMPATIBLE WITH SMART2200NET, SMART2200XLNET, SMART3000NET, SMART2200RMXL, SMARTINT3000, SMARTINT3000RM and other Tripp Lite UPS systems specifying the use of this pack.

Package Includes

- BP24V33 external battery pack
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with Tripp Lite UPS systems with a 24V DC external battery connection
- Supports stacking installation of two battery packs with the UPS on top
- Includes input and output connectors to support the connection of multiple battery packs for even longer extended run operation
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

Specifications

BATTERY	
Expandable battery runtime	Red female DC connector for additional battery packs
Connects to UPS via	3 ft. attached cable with red DC connector

DC system voltage	24 V DC
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	66
Unit Dimensions (HWD/in)	8 x 11.5 x 13
Material of construction	Putty color steel housing
Form factors supported	Floorstanding tower format. Stackable
CERTIFICATIONS	
Certifications	Tested to UL, cUL, CE, NOM
WARRANTY	
Product warranty	2 year product warranty
Optional coverage	3 year, 5 year, next day and on-site warranty coverage available

Related Items

Extended Warranties		
WEXT3-BP24V	3-Year Extended Warranty - For All 24V Battery Packs	Qty: [optional]
WEXT5-BP24V	5-Year Extended Warranty - For All 24V Battery Packs	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/EN/products/model.cfm?txtModelID=2484.