



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP24V70-3U

BP24V70-3U - External Battery Pack for UPS System

Highlights

Extends runtime of select compatible Tripp Lite UPS Systems with 24VDC external battery connector

Simple installation; 3U rackmount, tower and stack adaptable

Supports multi-battery pack installations via built-in daisychain connector

2-year warranty



Description

BP24V70-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 3 rack spaces (3U). Supports the connection of multiple BP24V70-3U battery packs via built-in daisychain connector. Includes heavy gauge cabling with high current DC connector for simple installation.

Compatible UPS Systems - OMNIVS1500XL, OMNIVSINT1500XL, SU750XL, SU750RTXL2U, SU1000XLa, SU1000RTXL2Ua, SUINT1000RTXL2Ua, SMART750RML2U and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP24V70-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports multi-battery pack installation via built-in daisychain connector
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

Specifications

BATTERY	
Connects to UPS via	Attached cable with red/black 75 amp male DC connector

DC system voltage	24V DC
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	176.37
Shipping weight (kg)	80.07
Shipping Dimensions (HWD/in)	11.25 x 23 x 31.5
Shipping Dimensions (HWD/cm)	28.56 x 58.42 x 80.01
Unit weight (lbs)	138.89
Unit weight (kg)	63.06
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25
Unit Dimensions (HWD/cm)	13.33 x 44.45 x 63.5
Material of construction	Steel
Form factors supported	3U rack/tower
WARRANTY	
Product warranty	2 year product warranty
Optional coverage	3 year, 5 year, next day and on-site warranty coverage available

Related Items

Extended Warranties		
WEXT3-BP24V	3-Year Extended Warranty - For All 24V Battery Packs	Qty: [optional]
WEXT5-BP24V	5-Year Extended Warranty - For All 24V Battery Packs	Qty: [optional]
Rackmount/Wallmount Kits		
2POSTRMKITWM	Universal 2-Post Rackmount Kit (Supports 2U to 4U UPS systems and battery packs.)	Qty: [optional]
Tower Stands		
2-9USTAND	Tower Stand - Expandable Tower Base Stand UPS Accessory	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/EN/products/model.cfm?txtModelID=3016.