



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP48V60-3UNAFTA

External Battery Pack for UPS System - NAFTA assembled version of BP48V60RT-3U

Highlights



- Extends runtime of select compatible Tripp Lite UPS Systems with 48VDC external battery connector
- Provides daisy-chain capability
- Simple installation; 3U rackmount, tower and stack adaptable
- 2-year warranty

Description

BP48V60-3UNAFTA rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 3 rack spaces (3U). Includes heavy gauge cabling with high current DC connector for simple installation. Additional output connector allows multiple BP48V60-3UNAFTA battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS - SM2200RMNAFTA, SM3000RMNAFTA, and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP48V60-3UNAFTA external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Additional output connector allows multiple BP48V60RT3U battery packs to be daisy-chained to the UPS for even longer extended run operation
- 2 year warranty

Specifications

BATTERY	
Expandable battery runtime	Blue 2-point battery connector

Connects to UPS via	Blue 2-point battery connector
DC system voltage	48VDC
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	200.6
Shipping weight (kg)	91.1
Shipping Dimensions (HWD/in)	11.25 x 23 x 31.5
Shipping Dimensions (HWD/cm)	28.6 x 58.4 x 80
Unit weight (lbs)	163.1
Unit weight (kg)	74
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25
Unit Dimensions (HWD/cm)	13.3 x 44.4 x 63.5
Material of construction	Steel
Form factors supported	3U rack/tower
ENVIRONMENTAL	
Operating Temperature	32-104 degrees F / 0-40 degrees C
WARRANTY	
Product warranty	2 year product warranty
Optional coverage	3 year, 5 year, next day and on-site warranty coverage available

Related Items

Extended Warranties		
WEXT5-BP48V60	5-Year Extended Warranty - For BP48V60RT3U	Qty: [optional]
WEXT3-BP48V60	3-Year Extended Warranty - For BP48V60RT3U	Qty: [optional]
Rackmount/Wallmount Kits		
2POSTRMKITWM	Universal 2-Post Rackmount Kit (Supports 2U to 4U UPS systems and battery packs.)	Qty: [optional]
Tower Stands		
2-9USTAND	Tower Stand - Expandable Tower Base Stand UPS Accessory	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/EN/products/model.cfm?txtModelID=3542.