

9 different sizes. Pull 1.5 oz. (42.5 gm)  
through 11.25 lbs. (5.1 kgm)

|                   | Catalog Number  | Voltage | Duty Cycle | Coil Power (Watts) | Pull (Ounces) |      |      |     | Weight (Ounces) |
|-------------------|-----------------|---------|------------|--------------------|---------------|------|------|-----|-----------------|
|                   |                 |         |            |                    | .125          | .250 | .500 | .75 |                 |
| <b>C7-18</b><br>  | C7-18C24DC-AY   | 24      | cont.      | 2.0                | 1.5           | 0.5  | ---  | --- | .5              |
|                   | C7-181024DC-AY  | 24      | 10%*       | 10.0               | 6.0           | 2.0  | ---  | --- | .5              |
|                   | C7-18C12DC-AY   | 12      | cont.      | 2.0                | 1.5           | 0.5  | ---  | --- | .5              |
|                   | C7-181012DC-AY  | 12      | 10%*       | 10.0               | 6.0           | 2.0  | ---  | --- | .5              |
| <b>C8-14</b><br>  | C8-14C24DC-AY   | 24      | cont.      | 2.4                | 0.8           | ---  | ---  | --- | 1               |
|                   | C8-141024DC-AY  | 24      | 10%*       | 7.0                | 3.0           | 0.5  | ---  | --- | 1               |
|                   | C8-14C12DC-AY   | 12      | cont.      | 2.4                | 0.8           | ---  | ---  | --- | 1               |
|                   | C8-141012DC-AY  | 12      | 10%*       | 7.0                | 3.0           | 0.5  | ---  | --- | 1               |
| <b>C8-24</b><br>  | C8-24C24DC-AY   | 24      | cont.      | 3.5                | 3.0           | 1.3  | 0.2  | --- | 1.5             |
|                   | C8-241024DC-AY  | 24      | 10%*       | 15.0               | 6.0           | 4.0  | 2.5  | 1.0 | 1.5             |
|                   | C8-24C12DC-AY   | 12      | cont.      | 3.5                | 3.0           | 1.3  | 0.2  | --- | 1.5             |
|                   | C8-241012DC-AY  | 12      | 10%*       | 15.0               | 6.0           | 4.0  | 2.5  | 1.0 | 1.5             |
| <b>C8-32</b><br>  | C8-32C24DC-AY   | 24      | cont.      | 4.0                | 2.5           | 1.5  | 1.0  | 0.8 | 2               |
|                   | C8-321024DC-AY  | 24      | 10%*       | 20.0               | 8.0           | 4.5  | 4.0  | 3.8 | 2               |
|                   | C8-32C12DC-AY   | 12      | cont.      | 4.0                | 2.5           | 1.5  | 1.0  | 0.8 | 2               |
|                   | C8-321012DC-AY  | 12      | 10%*       | 20.0               | 8.0           | 4.5  | 4.0  | 3.8 | 2               |
| <b>C12-24</b><br> | C12-24C24DC-AY  | 24      | cont.      | 3.5                | 7.0           | 3.0  | 1.5  | 0.5 | 3               |
|                   | C12-241024DC-AY | 24      | 10%*       | 22.0               | 21.0          | 13.0 | 7.0  | 3.0 | 3               |
|                   | C12-24C12DC-AY  | 12      | cont.      | 3.5                | 7.0           | 3.0  | 1.5  | 0.5 | 3               |
|                   | C12-241012DC-AY | 12      | 10%*       | 22.0               | 21.0          | 13.0 | 7.0  | 3.0 | 3               |