

<b>Product SKU:</b>	C1364.38.90
<b>Product Description:</b>	Speaker Wire, Superflex® <sup>®</sup> , No. of Conductors: 2, Gauge Size (AWG): 12, Conductor/Strands: 7x37/36, Jacket: Premium Grade Clear Superflex® <sup>®</sup> PVC, Temperature Range: -20°C to +60°C - Clear - 500 Ft. Reel
<b>Product Category:</b>	Electronics - Special Applications - Audio, Video, and Entertainment Cable - Superflex® <sup>®</sup> Speaker Wire - Parallel Construction

**Product Construction:**

Conductor:	<ul style="list-style-type: none"><li>12 AWG fully-annealed, stranded bare copper conductor per ASTM B-3</li></ul>
Insulation/Jacket:	<ul style="list-style-type: none"><li>Premium grade clear Superflex®<sup>®</sup> PVC</li><li>Temperature range: -20°C to +60°C</li></ul>

**Product Specification:**

No. of Conductors:	<ul style="list-style-type: none"><li>2</li></ul>
Conductor Size (AWG):	<ul style="list-style-type: none"><li>12</li></ul>
Conductor/Strands:	<ul style="list-style-type: none"><li>7x37/36</li></ul>
Jacket Color:	<ul style="list-style-type: none"><li>Clear</li></ul>
Nominal Insulation Thickness (in):	<ul style="list-style-type: none"><li>0.060</li></ul>
Nominal Insulation Thickness (mm):	<ul style="list-style-type: none"><li>1.52</li></ul>
Nominal Outside Diameter (in):	<ul style="list-style-type: none"><li>0.230 x 0.470</li></ul>
Nominal Outside Diameter (mm):	<ul style="list-style-type: none"><li>5.84 x 11.94</li></ul>
Standard Packaging:	<ul style="list-style-type: none"><li>500' Non-returnable Wood Reels</li></ul>
Standard Package Quantity:	<ul style="list-style-type: none"><li>1</li></ul>

UPC #:	<ul style="list-style-type: none"> <li>079407901913</li> </ul>
Put-up:	<ul style="list-style-type: none"> <li>500</li> </ul>
SCC-14:	<ul style="list-style-type: none"> <li>50079407901911</li> </ul>
Cube:	<ul style="list-style-type: none"> <li>1625.64</li> </ul>
Weight Per Unit of Measure:	<ul style="list-style-type: none"> <li>.08</li> </ul>
ColorOption:	<ul style="list-style-type: none"> <li>Clear</li> </ul>

## Product Information:

Applications:	<ul style="list-style-type: none"> <li>Hi-fi and stereo speaker wire</li> <li>Juke boxes</li> <li>Lamps</li> <li>Radios</li> <li>Suggested voltage rating: 120 Volts</li> <li>Not for in-wall use</li> </ul>
Compliances:	<ul style="list-style-type: none"> <li>UL Misc. (UL: 120V)</li> </ul>
Packaging:	<ul style="list-style-type: none"> <li>1000' (305 m) Spools</li> <li>500' (152 m) Spools</li> <li>Other put-ups available- consult Customer Service</li> </ul>

## Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)

**CAROL  
BRAND**