



Series C81/C91 Standard Dual Beam Wire Wrap Edge-Grip Sockets

FEATURES:

- Dual beam, edge-grip contacts provide high retention with positive wiping action.
- Removable cover provides lower profile.
- Side-to-side stackable.


SPECIFICATIONS:

- Body is black UL 94V-0 Glass-filled 4/6 Nylon.
- Dual beam contact is Grade A Phosphor Bronze Alloy, 1/2 hard.
- Contact plating: (all over 50 μ " [1.27 μ m] Nickel per SAE-AMS-QQ-N-290
Tin = 200 μ " [5.08 μ m] min Matte Tin per ASTM B545-97.
Tin/Lead = 50-150 μ " [1.27-3.81 μ m] min. 90/10 Tin/Lead per MIL-P-81728.
Gold = 10 μ " [0.25 μ m] min. Gold per MIL-G-45204.
- Contact current rating=1.5 Amp.
- Contact resistance=20 mOhms initial.
- Insulation resistance=100 MOhms @ 500 VDC per MIL-STD-1344, method 3003.1.
- Dielectric withstanding voltage=1000 VAC.
- Operating temperature= -67°F to 221°F [-55°C to 105°C] Tin
= -67°F to 257°F [-55°C to 125°C] Gold
- Solderability: MIL-STD-202, method 208 less heat aging.
- Accepts leads up to .011 x .018 x .003 [.28 x .46 x .08] or .021 [.53] diameter.
- Accepts leads .100-.200 [2.54-5.08] long with cover.


MOUNTING CONSIDERATIONS:

- Suggested PCB hole size=.046 \pm .002 [1.17 \pm .05] dia.

ALL DIMENSIONS: INCHES [MILLIMETERS]




All tolerances \pm .005 [.13] unless otherwise specified




Note: Aries specializes in custom design and production. In addition to the standard products shown on this page, special materials, platings, sizes, and configurations can be furnished, depending on quantities. Aries reserves the right to change product specifications without notice.

ORDERING INFORMATION



CONTACT DETAIL



No. of Pins	Dim. "A"	Dim. "B"	Centers "C"	Dim. "D" (max)	Dim. "E"
8	.465 [11.81]	.300 [7.62]	.300 [7.62]	.400 [10.16]	---
14	.765 [19.43]	.600 [15.24]	.300 [7.62]	.400 [10.16]	.300 [7.62]
16	.865 [21.97]	.700 [17.78]	.300 [7.62]	.400 [10.16]	.400 [10.16]
18	.965 [24.51]	.800 [20.32]	.300 [7.62]	.400 [10.16]	.400 [10.16]
20	1.065 [27.05]	.900 [22.86]	.300 [7.62]	.400 [10.16]	.400 [10.16]
22	1.180 [29.97]	1.000 [25.40]	.400 [10.16]	.500 [12.70]	.500 [12.70]
24	1.280 [32.51]	1.100 [27.94]	.600 [15.24]	.700 [17.78]	.500 [12.70]
28	1.480 [37.59]	1.300 [33.02]	.600 [15.24]	.700 [17.78]	.500 [12.70]
36	1.880 [47.75]	1.700 [43.18]	.600 [15.24]	.700 [17.78]	.800 [20.32]
40	2.080 [52.83]	1.900 [48.26]	.600 [15.24]	.700 [17.78]	.800 [20.32]



ARIES
ELECTRONICS, INC.

<http://www.arieselec.com> • info@arieselec.com

Bristol, PA USA
TEL: (215) 781-9956
FAX: (215) 781-9845



12003
REV. D