


JKL LAMP PART NO. (REFERENCE)	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms) @ 25°C	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
CF26349-28B	x = .325 y = .295	1715	730	5 ± 1	30,000 ± 3000	35,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
							TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP			
			DRAWN BY L. WENGSTROM		APP'VD BY DATE J.K. 1/29/03		SIZE A	FSCM NO. 55335	DRAWING NO. CF26349-28B	
RELEASED AND CANCEL P-0210-08 AND BF26349-28B			1/29/03							
REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET 1 OF 1
						NONE	1/29/03			