


**Specifications**




Nominal Size	23mm			
Impedance	8 Ohm ± 15%	at	1 KHz 1 V	
Resonant frequency	650 Hz ± 130 Hz	at	1 V	
Sound pressure level	89dB/w ± 3 dB	1 w 50 cm ave. at 0.8K, 1K, 1.2K, 1.5K Hz		
Response	Fo Hz ~ 18 KHz max 10 dB			
Input power	Nominal	1 W	Handling capacity	1.5 W
Operation	must be normal at program source 1 W			
Buzz, rattle, etc.	must be normal at sine wave 2.83 V			
Magnet	Size: 9.5 x 1.5 mm			
Load test	White noise	1 W	for	24 hours
Heat test	70 ± 2° C	20-50% R.H.	24 hours	
Humidity test	40 ± 2° C	90-95% R.H.	24 hours	

Frequency Response Curve

Potentiometer range	50 dB
Rectifier	RMS
Lower limit frequency	20 Hz
Wr. speed	100 mm/sec

Zero level 60 dB

REV.	DESCRIPTION	DATE
A	NEW DRAWING	7/3/2007



SPECIFICATIONS:
WIRE: UL1007, #28AWG
LENGTH: 152mm

TOLERANCE:
±0.5mm UNLESS OTHERWISE
SPECIFIED



CUI INC

20050 SW 112th Ave.
Tualatin, OR 97062
Phone: 503-612-2300
800-275-4899
Fax: 503-612-2383
Website: www.cui.com

TITLE: LOW PROFILE SPEAKER		REV: A
PART NO. CLS0231-L152	UNITS: MM [INCHES]	
DRAWN BY: ZRJ	APPROVED BY:	SCALE: 2:1

PC FILE NAME:
CLS0231-L152

COPYRIGHT 2007 BY CUI INC.