
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

© 2005, Projects Unlimited Inc.

SPECIFICATIONS

	REVISIONS		
LTR	DESCRIPTION	DATE	APPROVED
_	RELEASED FROM ENGINEERING	1/18/06	

PARAMETERS	VALUES	UNITS
RATED VOLTAGE (SQUARE WAVE)	3.6	Vp-p
OPERATING VOLTAGE RANGE	2.5 ~ 4.5	Vp-p
RATED CURRENT (MAX)	100	mΑ
COIL RESISTANCE	15±3	ОНМ
MINIMUM SPL @ 10 CM	85	dBA
RESONANT FREQUENCY	2700±500	Hz
OPERATING TEMPERATURE	-40 ~ +85	ů
STORAGE TEMPERATURE	-40 ~ +85	°C
HOUSING MATERIAL	LCP	_
TERMINAL MATERIAL	Sn PLATED BRASS	_
WEIGHT	0.4	grams



CHECKED

NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

APPROVED SMT-0827-S-R.DWG

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3'. APPROVALS DATE DRAWN J.A.F. 01/06

E.P.

B.R.

TRANSDUCER (ELECTRO-MECH)

Dayton , Ohio

DRAWING NO. SIZE 01/06 SMT-0827-S-R 01/06 SHEET 1 OF DO NOT SCALE DRAWING SCALE: N.T.S.