



# 0.6mm Pitch Stacking Height 3mm to 16mm Connector

## FX8, FX8C Series

FX8 Series



FX8C Series




Note that FX8 series and FX8C series are not mated with each other.


### ■Features

- 1. Stacking Height 3mm to 16mm available**  
The board to board stacking height can correspond to 3mm~16mm.
- 2. SMT Coplanarity**  
The coplanarity of the SMT solder area lead is maintained at the high accuracy of less than 0.1mm.
- 3. Mating Guide**  
The very small and guide rib is provided, and secures  $\pm 0.6\text{mm}$  self-alignment, considering the mating operativity into accounts.
- 4. Mis-insertion Prevention**  
The boss prevents mis-insertion in the board to cause due to the boss position and boss diameter.

#### ●Stacking Height 3,4mm-FX8 Series



#### ●Stacking Height 5 to 16mm-FX8C Series



### ■Applications

Note pc, business equipments, which require miniaturization or light-weight

**FX8, FX8C Series 0.6mm Pitch Stacking Height 3mm to 16mm Connector**

**FX8C Series**

**Product Specifications**

|        |                        |  |  |
|--------|------------------------|--|--|
| Rating | Current rating 0.4A    | Operating Temperature Range -55°C to +85°C Note 1. | Storage Temperature Range -10°C to +60°C Note 2. |
|        | Voltage rating 100V AC | Operating Humidity Range 40% to 80%                | Storage Humidity Range 40% to 70%                |

| Item                             | Specification  | Condition   |
|----------------------------------|--|---|
| 1. Insulation Resistance         | 100M ohms min.   | 250V DC   |
| 2. Withstanding voltage          | No flashover or insulation breakdown.                                    | 300V AC/1 minute  |
| 3. Contact Resistance            | 80m ohms max.  | 100mA   |
| 4. Vibration                     | No electrical discontinuity of 1μs or more                               | Frequency: 10 to 55 Hz, single amplitude of 0.75 mm, 2 hours in each of the 3 directions.               |
| 5. Humidity (Steady state)       | Contact resistance: 100m ohms max. Insulation resistance: 100M ohms min. | 96 hours at temperature of 40°C and humidity of 90% to 95%  |
| 6. Temperature Cycle             | Contact resistance: 100m ohms max. Insulation resistance: 100M ohms min. | (-55°C: 30 minutes, 15 to 35°C: 2 to 3 minutes<br>85°C: 30 minutes, 15 to 35°C: 2 to 3minutes) 5 cycles |
| 7. Durability (Mating/un-mating) | Contact resistance: 100m ohms max.                                       | 50 cycles   |
| 8. Resistance to Soldering heat  | No deformation of components affecting performance.                      | Reflow: At the recommended temperature profile<br>Manual soldering: 360°C for 5 seconds                 |

Note 1 : Includes temperature rise caused by current flow.

Note 2 : The term "storage" refers to products stored for long period of time prior to mounting and use. Operating Temperature Range and Humidity range covers non conducting condition of installed connectors in storage, shipment or during transportation.

Note 3 : Slight variations in color of the plastic compounds do not affect form ,fit or function of the connector.

Note 4 : FX8C-\*P-SV(\*),FX8C-\*S-SV(\*) is gold plated.

Note 5 : Information contained in this catalog represents general requirements for this Series. Contact us for the drawings and specifications for a specific part number shown.

**Material**

| Part               | Material        | Finish                    |                                   | Remarks |
|--------------------|-----------------|---------------------------|-----------------------------------|---------|
| Insulator          | PBS             | Light brown               |                                   | UL94V-0 |
| Header Contact     | Phosphor bronze | Contact area<br>Lead area | Gold plated<br>Tin plated(Note 4) | _____   |
| Receptacle Contact | Phosphor bronze | Contact area<br>Lead area | Gold plated<br>Tin plated(Note 4) | _____   |

**Ordering Information**

●Single Product

**FX8C - 120 P - SV 1 (91)**

①                      ②                      ③                      ④                      ⑤                      ⑥

|  |  |
|--|--|
| ① Series Name : FX8C                             | ⑤ Product height variation Blank : Standard (Minimum low profile)<br>1: +1mm . . . . . 3:+3mm      |
| ② Number of Contacts :60, 80, 90, 120, 140       | ⑥ Packaging Type<br>(71) : Tray packaging<br>(91) : Tube packaging<br>(92) : Embossed tape package |
| ③ Connector type      P :Header<br>S :Receptacle |  |
| ④ Contact type      SV :Board vertical type      |  |

●two-piece Connection Product

**FX8C - 120/120 P 11 - SV 1 J**



①                      ②                      ③                      ④                      ⑤                      ⑥                      ⑦

|   |  |
|---|--|
| ① Series Name :FX8C   | ④ Connector to Connector Pitch   |
| ② Number of Contacts: 60×2, 80×2, 90×2,<br>100×2, 120×2, 140×2<br>Example: 120/120 = 240 contacts | ⑤ Contact type      SV : Board vertical type   |
| ③ Connector Type :      P : Header<br>S : Receptacle  | ⑥ Product Height Variation Blank : Standard (Minimum lot profile)<br>1:+1mm . . . . . 3:+3mm |
|   | ⑦ J: two-piece connection product  |



\*The standard packaging of the two-piece connection product is the tray packaging.

## Stacking Height Variation

| Header \ Receptacle                 | FX8C-**-S-SV<br>FX8C-**-**S11-SVJ | FX8C-**-S-SV5<br>FX8C-**-**S11-SV5J |
|-------------------------------------|-----------------------------------|-------------------------------------|
| FX8C-**-P-SV<br>FX8C-**-**P11-SVJ   | 5mm                               | 10mm                                |
| FX8C-**-P-SV1<br>FX8C-**-**P11-SV1J | 6mm                               | 11mm                                |
| FX8C-**-P-SV2<br>FX8C-**-**P11-SV2J | 7mm                               | 12mm                                |
| FX8C-**-P-SV4<br>FX8C-**-**P11-SV4J | 9mm                               | 14mm                                |
| FX8C-**-P-SV6<br>FX8C-**-**P11-SV6J | 11mm                              | 16mm                                |



## Header (Single Product) [FX8C-\*\*-P-SV]



Unit:mm



| Part Number      | CL No.        | Number of Contacts | A     | B     | C     | D     | E     | Tube packaging Quantity (Pieces) | RoHS |
|------------------|---------------|--------------------|-------|-------|-------|-------|-------|----------------------------------|------|
| FX8C- 60P-SV(92) | 578-0501-9-92 | 60                 | 24.60 | 23.00 | 20.70 | 17.40 | 22.20 | 21                               | YES  |
| FX8C- 80P-SV(92) | 578-0503-4-92 | 80                 | 30.60 | 29.00 | 26.70 | 23.40 | 28.20 | 17                               |      |
| FX8C-100P-SV(92) | 578-0505-0-92 | 100                | 36.60 | 35.00 | 32.70 | 29.40 | 34.20 | 14                               |      |
| FX8C-120P-SV(92) | 578-0506-2-92 | 120                | 42.60 | 41.00 | 38.70 | 35.40 | 40.20 | 12                               |      |
| FX8C-140P-SV(92) | 578-0507-5-92 | 140                | 48.60 | 47.00 | 44.70 | 41.40 | 46.20 | 10                               |      |

\*\*71: Tray packaging product 91: Tube packaging product  
 92: Embossed tape packaging product  
 Note 1: To order the tube packaging product, please determine the quantity for delivery, multiplying the tube packaging product by an integer.

Note 2: The embossed tape packaging product is prepared for 60 and 80 contacts only. In addition, the product will be procured per reel unit. Please refer to the delivery form item on page A182 for details.

Note 3: Tray packaging product is not for board placement with automatic equipment.

[FX8C-\*\*-P-SV1]  
 [FX8C-\*\*-P-SV2]  
 [FX8C-\*\*-P-SV4]  
 [FX8C-\*\*-P-SV6]





Unit: mm

| Part Number       | CL No.        | Number of Contacts | A     | B     | C     | D     | E     | F     | Tube packaging Quantity (Pieces) | RoHS |
|-------------------|---------------|--------------------|-------|-------|-------|-------|-------|-------|----------------------------------|------|
| FX8C- 60P-SV1(92) | 578-0521-6-92 | 60                 | 24.60 | 23.00 | 20.70 | 17.40 | 22.20 | 5.45  | 21                               | YES  |
| FX8C- 60P-SV2(92) | 578-0541-3-92 |                    |       |       |       |       |       | 6.45  |                                  |      |
| FX8C- 60P-SV4(92) | 578-0581-8-92 |                    |       |       |       |       |       | 8.45  |                                  |      |
| FX8C- 60P-SV6(92) | 578-0601-3-92 |                    |       |       |       |       |       | 10.45 |                                  |      |
| FX8C- 80P-SV1(92) | 578-0523-1-92 | 80                 | 30.60 | 29.00 | 26.70 | 23.40 | 28.20 | 5.45  | 17                               | YES  |
| FX8C- 80P-SV2(92) | 578-0543-9-92 |                    |       |       |       |       |       | 6.45  |                                  |      |
| FX8C- 80P-SV4(92) | 578-0583-3-92 |                    |       |       |       |       |       | 8.45  |                                  |      |
| FX8C- 80P-SV6(92) | 578-0603-9-92 |                    |       |       |       |       |       | 10.45 |                                  |      |
| FX8C-100P-SV1(92) | 578-0525-7-92 | 100                | 36.60 | 35.00 | 32.70 | 29.40 | 34.20 | 5.45  | 14                               | YES  |
| FX8C-100P-SV2(92) | 578-0545-4-92 |                    |       |       |       |       |       | 6.45  |                                  |      |
| FX8C-100P-SV4(92) | 578-0585-9-92 |                    |       |       |       |       |       | 8.45  |                                  |      |
| FX8C-100P-SV6(92) | 578-0605-4-92 |                    |       |       |       |       |       | 10.45 |                                  |      |
| FX8C-120P-SV1(92) | 578-0526-0-92 | 120                | 42.60 | 41.00 | 38.70 | 35.40 | 40.20 | 5.45  | 12                               | YES  |
| FX8C-120P-SV2(92) | 578-0546-7-92 |                    |       |       |       |       |       | 6.45  |                                  |      |
| FX8C-120P-SV4(92) | 578-0586-1-92 |                    |       |       |       |       |       | 8.45  |                                  |      |
| FX8C-120P-SV6(92) | 578-0606-7-92 |                    |       |       |       |       |       | 10.45 |                                  |      |
| FX8C-140P-SV1(92) | 578-0527-2-92 | 140                | 48.60 | 47.00 | 44.70 | 41.40 | 46.20 | 5.45  | 10                               | YES  |
| FX8C-140P-SV2(92) | 578-0547-0-92 |                    |       |       |       |       |       | 6.45  |                                  |      |
| FX8C-140P-SV4(92) | 578-0587-4-92 |                    |       |       |       |       |       | 8.45  |                                  |      |
| FX8C-140P-SV6(93) | 578-0607-0-93 |                    |       |       |       |       |       | 10.45 |                                  |      |

Note 5

\*\* 71: Tray packaging product 91: Tube packaging product 92: Embossed tape packaging product  
 Note 1: To order the tube packaging product, please determine a quantity for delivery, multiplying the tube packaging product by an integer.  
 Note 2: The embossed tape packaging product is prepared for 60 and 80 contacts only. In addition, the product will be sold per reel unit. Please refer to the packaging specification item on page A182 for details.  
 Note 3: The locator material is installed between leads for the FX8C-P-SV6 type.  
 Note 4: Tray packaging product is not for board placement with automatic equipment.  
 Note 5: (93) spec is with vacuum pick-up tape, embossed tape packaging product.

## ■ Receptacle (Single Product) [FX8C-\*\*-S-SV]




Unit:mm

| Part Number      | CL No.        | Number of Contacts | A     | B     | C     | D     | E     | Tube packaging Quantity (Pieces) | RoHS |
|------------------|---------------|--------------------|-------|-------|-------|-------|-------|----------------------------------|------|
| FX8C- 60S-SV(92) | 578-0801-2-92 | 60                 | 24.60 | 23.05 | 20.80 | 17.40 | 22.20 | 21                               | YES  |
| FX8C- 80S-SV(92) | 578-0803-8-92 | 80                 | 30.60 | 29.05 | 26.80 | 23.40 | 28.20 | 17                               |      |
| FX8C-100S-SV(92) | 578-0805-3-92 | 100                | 36.60 | 35.05 | 32.80 | 29.40 | 34.20 | 14                               |      |
| FX8C-120S-SV(92) | 578-0806-6-92 | 120                | 42.60 | 41.05 | 38.80 | 35.40 | 40.20 | 12                               |      |
| FX8C-140S-SV(92) | 578-0807-9-92 | 140                | 48.60 | 47.05 | 44.80 | 41.40 | 46.20 | 10                               |      |

\*\* 71: Tray packaging product 91: Tube packaging product 92: Embossed tape packaging product  
 Note 1: To order the tube packaging product, please determine a quantity for delivery, multiplying the tube packaging product by an integer.  
 Note 2: The embossed tape packaging product is prepared for 60 and 80 contacts only. In addition, the product will be procured per reel unit. Please refer to the packaging specification item on page A182 for details.  
 Note 3: Tray packaging product is not for board placement with automatic equipment.

## [FX8C-\*\*-S-SV5]





Unit:mm



| Part Number       | CL No.        | Number of Contacts | A     | B     | C     | D     | E     | Tube packaging Quantity (Pieces) | RoHS |
|-------------------|---------------|--------------------|-------|-------|-------|-------|-------|----------------------------------|------|
| FX8C- 60S-SV5(92) | 578-0821-0-92 | 60                 | 24.60 | 23.05 | 20.80 | 17.40 | 22.20 | 21                               | YES  |
| FX8C- 80S-SV5(92) | 578-0823-5-92 | 80                 | 30.60 | 29.05 | 26.80 | 23.40 | 28.20 | 17                               |      |
| FX8C-100S-SV5(92) | 578-0825-0-92 | 100                | 36.60 | 35.05 | 32.80 | 29.40 | 34.20 | 14                               |      |
| FX8C-120S-SV5(92) | 578-0826-3-92 | 120                | 42.60 | 41.05 | 38.80 | 35.40 | 40.20 | 12                               |      |
| FX8C-140S-SV5(92) | 578-0827-6-92 | 140                | 48.60 | 47.05 | 44.80 | 41.40 | 46.20 | 10                               |      |

\*\* 71: Tray packaging product 91: Tube packaging product 92: Embossed tape packaging product  
 Note 1: To order the tube packaging product, please determine a quantity for delivery, multiplying the tube packaging product by an integer.  
 Note 2: The embossed tape package product is prepared for 60 and 80 contacts only. In addition, the product will be procured per reel unit. Please refer to the packaging specification item on page A182 for details.  
 Note 3: Tray packaging product is not for board placement with automatic equipment.

## ◆ PCB mounting pattern



## Header (two-pieces Connection Product) [FX8C-\*/\*/\*P11-SVJ]





Unit:mm

| Part Number             | CL No.        | Number of Contacts | A     | B     | C     | D     | E     | F     | RoHS |
|-------------------------|---------------|--------------------|-------|-------|-------|-------|-------|-------|------|
| FX8C- 60/ 60P11-SVJ(71) | 578-0651-1-71 | 60×2               | 31.70 | 24.70 | 23.00 | 20.70 | 17.40 | 22.20 | YES  |
| FX8C- 80/ 80P11-SVJ(71) | 578-0653-7-71 | 80×2               | 37.70 | 30.70 | 29.00 | 26.70 | 23.40 | 28.20 |      |
| FX8C-100/100P11-SVJ(71) | 578-0655-2-71 | 100×2              | 43.70 | 36.70 | 35.00 | 32.70 | 29.40 | 34.20 |      |
| FX8C-120/120P11-SVJ(71) | 578-0656-5-71 | 120×2              | 49.70 | 42.70 | 41.00 | 38.70 | 35.40 | 40.20 |      |
| FX8C-140/140P11-SVJ(71) | 578-0657-8-71 | 140×2              | 55.70 | 48.70 | 47.00 | 44.70 | 41.40 | 46.20 |      |

Note 1: The two-piece connection product is packaged by tray.

Note 2: Tray packaging product is not for board placement with automatic equipment.

- [FX8C-\*/\*/\*P11-SV1J]
- [FX8C-\*/\*/\*P11-SV2J]
- [FX8C-\*/\*/\*P11-SV4J]
- [FX8C-\*/\*/\*P11-SV6J]



Unit: mm

| Part Number              | CL No.        | Number of Contacts | A     | B     | C     | D     | E     | F     | G    | H     | RoHS |
|--------------------------|---------------|--------------------|-------|-------|-------|-------|-------|-------|------|-------|------|
| FX8C- 60/ 60P11-SV1J(71) | 578-0671-9-71 | 60×2               | 31.70 | 24.70 | 23.00 | 20.70 | 17.40 | 22.20 | 4.35 | 5.45  | YES  |
| FX8C- 60/ 60P11-SV2J(71) | 578-0691-6-71 |                    |       |       |       |       |       |       | 5.35 | 6.45  |      |
| FX8C- 60/ 60P11-SV4J(71) | 578-0731-9-71 |                    |       |       |       |       |       |       | 7.35 | 8.45  |      |
| FX8C- 60/ 60P11-SV6J(71) | 578-0751-6-71 |                    |       |       |       |       |       |       | 9.35 | 10.45 |      |
| FX8C- 80/ 80P11-SV1J(71) | 578-0673-4-71 | 80×2               | 37.70 | 30.70 | 29.00 | 26.70 | 23.40 | 28.20 | 4.35 | 5.45  |      |
| FX8C- 80/ 80P11-SV2J(71) | 578-0693-1-71 |                    |       |       |       |       |       |       | 5.35 | 6.45  |      |
| FX8C- 80/ 80P11-SV4J(71) | 578-0733-4-71 |                    |       |       |       |       |       |       | 7.35 | 8.45  |      |
| FX8C- 80/ 80P11-SV6J(71) | 578-0753-1-71 |                    |       |       |       |       |       |       | 9.35 | 10.45 |      |
| FX8C-100/100P11-SV1J(71) | 578-0675-0-71 | 100×2              | 43.70 | 36.70 | 35.00 | 32.70 | 29.40 | 34.20 | 4.35 | 5.45  |      |
| FX8C-100/100P11-SV2J(71) | 578-0695-7-71 |                    |       |       |       |       |       |       | 5.35 | 6.45  |      |
| FX8C-100/100P11-SV4J(71) | 578-0735-0-71 |                    |       |       |       |       |       |       | 7.35 | 8.45  |      |
| FX8C-100/100P11-SV6J(71) | 578-0755-7-71 |                    |       |       |       |       |       |       | 9.35 | 10.45 |      |
| FX8C-120/120P11-SV1J(71) | 578-0676-2-71 | 120×2              | 49.70 | 42.70 | 41.00 | 38.70 | 35.40 | 40.20 | 4.35 | 5.45  |      |
| FX8C-120/120P11-SV2J(71) | 578-0696-0-71 |                    |       |       |       |       |       |       | 5.35 | 6.45  |      |
| FX8C-120/120P11-SV4J(71) | 578-0736-2-71 |                    |       |       |       |       |       |       | 7.35 | 8.45  |      |
| FX8C-120/120P11-SV6J(71) | 578-0756-0-71 |                    |       |       |       |       |       |       | 9.35 | 10.45 |      |
| FX8C-140/140P11-SV1J(71) | 578-0677-5-71 | 140×2              | 55.70 | 48.70 | 47.00 | 44.70 | 41.40 | 46.20 | 4.35 | 5.45  |      |
| FX8C-140/140P11-SV2J(71) | 578-0697-2-71 |                    |       |       |       |       |       |       | 5.35 | 6.45  |      |
| FX8C-140/140P11-SV4J(71) | 578-0737-5-71 |                    |       |       |       |       |       |       | 7.35 | 8.45  |      |
| FX8C-140/140P11-SV6J(71) | 578-0757-2-71 |                    |       |       |       |       |       |       | 9.35 | 10.45 |      |

Note 1: The two-piece connection product is packaged by tray.

Note 2: Tray packaging product is not for board placement with automatic equipment.


Note 3: The locator material is installed between leads for the FX8C-\*/\*/\*P11-SV6J type.




FX8, FX8C Series 0.6mm Pitch Stacking Height 5mm to 16mm Connector

◆ Detailed Figure After Joint Removal  
 (Single Product in two-piece Connection Product)

Header



Receptacle





## ◆ Packaging Type

| Packaging Type          | Number of Contacts      | 60 contacts  | 80 contacts | 100 contacts | 120 contacts | 140 contacts |
|-------------------------|-------------------------|--|-------------|--------------|--------------|--------------|
| Tube packaging          | Packaged Product Pieces | 21 pieces  | 17 pieces   | 14 pieces    | 12-pieces    | 10pieces     |
|                         | Sales Unit              | Deliver the multiplied pieces. (Example) In case of 20 contacts,21 pieces, 4two-pieces,... |             |              |              |              |
|                         | Total Tube Length       | 550mm±2mm  |             |              |              |              |
| Embossed Tape Packaging | Tape Width              | 44mm   |             | 56mm         |              | 72mm         |
|                         | Product Pitch           | 12mm   |             |              |              |              |
|                         | Emboss Reel Diameter    | Refer to the table on page A183 in this catalog.   |             |              |              |              |
|                         | Packaged Product Pieces | Refer to the table on page A183 in this catalog.   |             |              |              |              |
|                         | Sales Unit              | Per reel   |             |              |              |              |


\*The above packaging type is , as listed for the single product only.  
 In addition, the packaging type of the two-piece connection product is the tray packaging.

## ◆ Packaging Specification

### [Tube packaging]


#### ● Header

- [FX8-\*\*\*P-SV (91)]
- [FX8-\*\*\*P-SV1 (91)]
- [FX8-\*\*\*P-SV2 (91)]
- [FX8-\*\*\*P-SV4 (91)]
- [FX8-\*\*\*P-SV6 (91)]



#### ● Receptacle


- [FX8C-\*\*\*S-SV (91)]
- [FX8C-\*\*\*S-SV5 (91)]



| P/S        | Part Number        | A    |
|------------|--------------------|------|
| Header     | FX8C-***P-SV (91)  | 9    |
|            | FX8C-***P-SV1 (91) | 10   |
|            | FX8C-***P-SV2 (91) | 11   |
|            | FX8C-***P-SV4 (91) | 13   |
|            | FX8C-***P-SV6 (91) | 15   |
| Receptacle | FX8C-***S-SV (91)  | 7.4  |
|            | FX8C-***S-SV5 (91) | 12.4 |

## [Embossed Tape Package]

### ●Carrier Size Pattern



Unit: mm

| P/S        | Part Number        | A   | B   | C    | D   | E    | Product Pieces |
|------------|--------------------|-----|-----|------|-----|------|----------------|
| Header     | FX8C-**-P-SV (92)  | 5.5 | 7.9 | 5.2  | 1.2 | φ370 | 1000 pieces    |
|            | FX8C-**-P-SV1 (92) | 5.5 | 7.9 | 6.2  | 1.2 | φ370 | 1000 pieces    |
|            | FX8C-**-P-SV2 (92) | 5.5 | 7.9 | 7.2  | 1.2 | φ330 | 500 pieces     |
|            | FX8C-**-P-SV4 (92) | 5.5 | 7.9 | 9.2  | 1.2 | φ370 | 500 pieces     |
|            | FX8C-**-P-SV6 (92) | 5.5 | 7.9 | 11.2 | 1.2 | φ370 | 500 pieces     |
| Receptacle | FX8C-**-S-SV (92)  | 6.0 | 8.4 | 4.3  | 1.2 | φ330 | 1000 pieces    |
|            | FX8C-**-S-SV5 (92) | 6.0 | 8.4 | 9.3  | 1.2 | φ370 | 500 pieces     |


Note 2

Note 1

Note 2

\*\* : Number of Contacts

### ●Reel State Size Pattern (FREE)



Note 1: E dimension for FX8C-140S-SV(92) is φ370, core dia. is φ100.

Note 2: E dimension for FX8C-120P-SV2(92), FX8C-120S-SV5(92), FX8C-140S-SV5(92) is φ380.