

Industrial and Commercial

G84-4400 Ultraslim Series Keyboards



Main Applications

- Rack Mount Systems
- Airlines
- Banking
- Education/Schools
- Manufacturing
- Medical Equipment
- Automotive Equipment
- Office/Data Entry
- White Box PCs
- Field Services
- Test Equipment
- Kiosk Applications
- POS/POT
- Transport

Key Features

- Mechanical Keyswitches are Rated at 50 Million Actuations to Withstand Harsh Environments and Ensure Long Product Lifetime
- Size-reduced QWERTY Key Layout in Ultraslim 15" Form Factor Combines Maximal Space Efficiency with Comfortable Alphanumeric Data Entry
- "FN-Key" for Easy Access of Integrated Numeric Area Ensures Complete Function Support as with Full Size Keyboards
- All Available with PS/2 and USB Interface.
- Ultraflat Optical Trackball for Easy Cursor Navigation at Minimized Space
- "Non-Windows" Key Layout

Main Part Numbers

G84-4400PUBUS-0

Light grey 15" ultraslim USB keyboard with mechanical trackball. US space reduced 83 position key layout without 'Windows keys', 2 PS/2 connectors. Mechanical keyswitches with tampoprinted keycaps.

G84-4420LPBEU-2

Black 15" ultraslim PS/2 keyboard with optical trackball. US space reduced 83 position key layout without 'Windows keys', 2 PS/2 connectors. Mechanical keyswitches with laser etched keycaps.

G84-4420LUBEU-2

Black 15" ultraslim USB keyboard with optical trackball. US space reduced 83 position key layout. Mechanical keyswitches with laser etched keycaps.

All models available in light grey and black.

Additional product versions on request.



Industrial and Commercial

G84-4400 Ultraslim Series Keyboards

Part Number Legend



Technical Data

Interface

PS/2, USB

Current Input

max. 100 mA

Trackball

Diameter: 16mm

Two switch-activated mouse buttons Mechanical and optical versions available.

Cable Length

Approx. 1.75 m

Key Layout

Sized reduced 83 key layout

Weight (without/with packaging)

0.6/0.7 kg

Dimension

370 x 139 x 20 mm (keyboard) 372 x 141 x 22 mm (packaging)

Packaging Units

21 per master carton12 master cartons per pallet

Keyswitch Lifetime

50 million operations

Storage Temperature

-20°C to 60°C

Operating Temperature

0°C to 50°C

Approvals

cURus, FCC, CE, VDE, C-Tick, VCCI, GOST-R (PS/2 version also: RRL, BSMI)

Delivery Volume

Keyboard, Quick Guide,

Warranty

2 years

For information on repairs or warranty status contact: Cherry Technical Support Phone: 800.510.1689

E-Mail: keyboardsupport@cherrycorp.com

Contact

Call, fax or visit our website for more information.

Cherry Electrical Products

11200 88th Avenue Pleasant Prairie, WI 53158

Phone: Web: 262.942.6500 www.cherrycorp.com

E-Mail: sales@cherrycorp.com Fax: 262.942.6566 The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

Last Update: 10/15/08

© 2008 Cherry Electrical Products