

Ultralim Trackball Keyboard

G84-4420

This high-quality compact keyboard with integrated optical Trackball is designed for all applications where reliability, reduced space requirements and low height are of great importance. Useful for IT, industrial usage and medical facilities. Equally suitable for 19 inch rack-mounted drawers.



Facts & Features

- Single mechanical keys with Gold Crosspoint contacts (Cherry ML Modules)
- Designed for continuous use – more than 20 Mio. key presses
- Robust and reliable with precise key actuation
- Integrated high quality **Optical Trackball** plus 2 mouse buttons
- Ultra slim - only 20 mm overall height
- Lightweight
- Usable with standard drivers of the operating system
- Ideal for industrial usage with space limitations and for 19" applications
- Also available without housing for OEM

Agency Approvals

- CE, VDE/ÜG (EN60950), FCC, cUR, VCCI, BSMI, C-Tick, GOST-R
- Designed for MS Windows® XP
- MS Windows® Vista, Linux compatible

Delivery Volume

- Keyboard, Manual

System Requirements

- PS/2: Plugs for Keyboard and Mouse
- USB: USB plug & supporting operating system

Technical Data

- Interface
USB or 2x PS/2
- Technology (USB Variant)
USB 2.0 (1.1 compatible), HID conform
Bus powered, composite device, low speed
- Cable Length
approx. 1.75 m
- Number of Keys
83 = intern. layout without Windows™ keys
84 = europ. layout without Windows™ keys
Integrated Numeric Keypad
- Trackball
Scanning: contactless, optical
Resolution: 400 dpi
- Weight
approx. 563 g (keyboard)
approx. 720 g (without packaging)
- Dimensions
approx. 370 x 139 x 19,6 mm (keyboard)
approx. 400 x 195 x 32 mm (packaging)
- Current Input (3 LEDs on)
USB: typ. 36 mA
PS/2: typ. 24 mA (keyboard)
typ. 11 mA (trackball)
- Reliability
MCBF > 10⁹ operations
MTBF > 100.000 hours
- Storage Temperature
-20 °C to 60 °C
- Operating Temperature
0 °C to 40 °C
- Operating life time of individual keys
> 20 Mio operations
- Packaging Unit
140 keyboards per master carton
2 master cartons per pallet
- Warranty
2 years

Order Description

<i>Order Number</i>	<i>Trackball Scanning</i>	<i>Interface</i>	<i>Colour</i>
G84-4420LUBxx-0	optical	USB	light grey
G84-4420LUBxx-2	optical	USB	black
G84-4420LPBxx-0	optical	2 x PS/2	light grey
G84-4420LPBxx-2	optical	2 x PS/2	black

The xx in the order number defines the country version:

Possible european layouts:

BE	Belgium
CH	Switzerland
DE	Germany
DK	Denmark
ES	Spain
FR	France
GB	UK-English
HU	Hungary
IT	Italy
NO	Norway
PL	Poland
PO	Portugal
SF	Sweden / Finland
SK	Slovakia
TS	Czech Republic
TQ	Turkey

Possible international layouts:

EU	US English with €
JK	Japan
KR	US-English / Korea
RB	US-English / Cyrillic
RC	US-English / China

Cherry GmbH
Cherrystraße
91275 Auerbach/Opf.
Germany

(Other country versions upon request)

Phone: +49 9643 18 0
Internet: www.cherry.de

Sales: +49 1805 243779 (+49 1805 CHERRY)
E-Mail: sales@cherry.de
Fax: +49 9643 18 1545

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.
Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2008 Cherry GmbH, Last update: Jan 07, 2008_V02

