





All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor.  
Property of FCI. Copyright FCI.



LAY-OUT  
P.C.B. - HOLE  
(FRONT SIDE)



## PERFORMANCE CHARACTERISTICS

1.5A AT 20°C (FULLY LOADED)

1 A AT 70°C (FULLY LOADED)

RATED VOLTAGE : 500 V AC (CONT /CONT)

OPERATING TEMPERATURE : -55°C TO 125°C

CONTACT RESISTANCE 20 MO MAX

INSERTION FORCE : 0.75N MAX/CONT

EXTRACTION FORCE : 0.15N MIN/CONT

INSULATION RESISTANCE :  $10^4$  MΩ MIN

## NOTES

WIRING  
 LEAD FREE INDICATOR :LF=LEAD FREE  
 1. "      "      "  
 PERFORMANCE LEVEL INDICATOR  
 (REF. Dwg. No. BSC-2018A4-002)

2. THIS PRODUCT IS CSA APPROVED.  
THIS PRODUCT IS UL RECOGNIZED.
3. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :BS.A.201572.001
4. THIS PRODUCT (LFI) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008