



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: HT10DBS

### Isobar Home/Business Theater Surge Suppressor - Premium-performance surge and line noise protection for all components



#### Highlights

- 10 outlets / 8-ft. cord
- 3570 joule rating
- Isolated Filter Banks / all-metal housing
- 3-line coaxial (gold) surge protection
- 1-line tel/modem and 1-line network (100BaseT, high-speed) surge protection
- \$500,000 [Ultimate Lifetime Insurance](#) (USA and Canada only)

#### Description

Tripp Lite's HT10DBS Isobar Home/Business Theater Surge Suppressor provides premium protection--3570 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for medium-to-large home/business theater installations: high-definition TVs, PVRs, satellite and A/V receivers, subwoofers, DVD/CD players and more. Exclusive Isolated Filter Banks eliminate noise interference between components. 10 outlets (with transformer spacing and plug-in safety covers), 3-line coaxial protection, 1-line tel/modem protection and 1-line network (100BaseT, high-speed) protection safeguard an entire home/business theater system. \$500,000 [Ultimate Lifetime Insurance](#) coverage (USA and Canada only). Includes all-metal housing, color-coordinated outlet/plug labels, three diagnostic LEDs, 8-ft. cord with a right-angle plug, 6-ft. gold coax cable, 6-ft. phone cord and 6-ft. network cable.

#### Applications

Perfect for medium-to-large home/business theater installations: high-definition TVs, PVRs, satellite and A/V receivers, subwoofers, DVD/CD players and more.

#### Package Includes

- HT10DBS Home/Business Theater Surge Suppressor
- 6-ft. DSS cable
- 6-ft. phone cord
- 6-ft. network cable
- Instruction manual with warranty information

#### Features

- 3570 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- \$500,000 [Ultimate Lifetime Insurance](#) (USA and Canada only) covers connected components against surge damage...for life!
- Isolated Filter Banks eliminate interference between connected components
- All-metal housing safely withstands the strongest surges
- 10 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system
- Widely spaced outlets accommodate up to 6 transformers

Four plug-in safety covers protect against accidental contact with unused outlets

3 sets of surge-protected Type F gold coaxial connectors (with included 6-ft. gold coax cable) safeguard components on cable, satellite and antenna line

1-line tel/modem and 1-line network (100BaseT, high-speed) surge protection (with included 6-ft. phone cord and 6-ft. network cable) safeguards personal video recorders (PVRs) on up to two lines simultaneously.

8-ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system

3 diagnostic LEDs alert user to protection, line power and ground status

Keyhole slots provide convenient wall or cabinet mounting

Illuminated master switch provides one-touch power control over all components. Circuit breaker protects against dangerous system overload

All-metal housing (black) stands up to the most demanding environments

UL and cUL listed

Lifetime product warranty

Color-coordinated outlet/plug labels

## Specifications

<b>SYSTEM OVERVIEW</b>	
<b>Voltage compatibility</b>	120 VAC
<b>Frequency compatibility</b>	50/60 Hz
<b>OUTPUT</b>	
<b>Output volt amp capacity (amps)</b>	12
<b>Output watts</b>	1440
<b>Outlet quantity / type</b>	10 NEMA 5-15R
<b>Transformer accommodation</b>	Accommodates 6 transformers
<b>INPUT</b>	
<b>Input connection type</b>	NEMA 5-15P
<b>Input cord gauge, type</b>	14 gauge, SJT
<b>Input cord length (ft.)</b>	8 ft.
<b>Input cord length (m)</b>	2.4
<b>Recommended Electrical Service</b>	120V (110-125V)
<b>Input plug features</b>	Space-saving right-angle input plug
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>Diagnostic LEDs</b>	Built-in LEDs confirm line power, protection and ground status
<b>Switches</b>	Combination AC circuit breaker and illuminated 2 position on/off power switch
<b>SURGE / NOISE SUPPRESSION</b>	
<b>Protection modes</b>	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
<b>AC suppression joule rating</b>	3570 joules
<b>Clamping voltage (RMS)</b>	140V
<b>AC suppression response time</b>	NM = instantaneous CM = < 1 ns
<b>UL1499 let through rating</b>	330V - UL verified
<b>EMI / RFI filtering</b>	Up to 60 dB
<b>DATALINE SURGE SUPPRESSION</b>	
<b>Telephone/DSL Protection</b>	Yes
<b>Telephone/DSL Protection Details</b>	1 line
<b>Cable (Coax) Protection</b>	Yes

<b>Cable (Coax) Protection Details</b>	3 line
<b>Network (Ethernet) Protection</b>	Yes
<b>PHYSICAL</b>	
<b>Unit weight (lbs)</b>	3.5
<b>Unit weight (kg)</b>	1.6
<b>Unit Dimensions (HWD/in)</b>	14.25 x 2.25 x 3.5
<b>Unit Dimensions (HWD/cm)</b>	36.2 x 2 x 5.7
<b>Material of construction</b>	Metal
<b>Integrated keyhole mounting tabs</b>	Keyhole mounting slots allow desk or wall mounting
<b>AC line cord color</b>	Black
<b>Style</b>	Strip
<b>CERTIFICATIONS</b>	
<b>UL1449 1998 Rev. (AC Suppression)</b>	UL1449
<b>UL1363 (Power Tap)</b>	UL1363
<b>UL497A (Communications)</b>	UL497A
<b>FCC Part 68 (Communications)</b>	FCC Part 68
<b>cUL / CSA (Canada)</b>	cUL
<b>Approvals</b>	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
<b>Product warranty</b>	Lifetime
<b>Connected equipment insurance (USA and Canada Only)</b>	\$500,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/EN/products/model.cfm?txtModelID=2813](http://www.tripplite.com/EN/products/model.cfm?txtModelID=2813).