






REV.	DESCRIPTION	DATE
A	NEW DRAWING	4/11/2005
B	Added pin dimensions	5/4/2006
C	PCB layout clarification	12/14/2007



PCB LAYOUT
TOP VIEW



TOLERANCE:
X.X ±0.2mm
X.XX ±0.1mm
X.XXX ±0.05mm



SPECIFICATIONS:
 RATING: 12V DC @ 2A; 100V AC @ 1A
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 50M OHMS MIN: 250V DC
 VOLTAGE WITHSTAND: 250V AC R.M.S. FOR 1 MINUTE
 INSERTION FORCE: 4.5KG MAX
 WITHDRAWAL FORCE: 0.8KG~3.5KG
 LIFE: 5,000 CYCLES

	MATERIAL	PLATING
TERMINALS (1-6)	Phosphor Bronze	Silver
EARTH TERMINAL	Brass	Tin
HOUSING	PBT	



CUI INC

20050 SW 112th Ave.
 Tualatin, OR 97062
 Phone: 503-612-2300
 800-275-4899
 Fax: 503-612-2383
 Website: www.cui.com

TITLE:	MINIATURE CIRCULAR DIN CONNECTOR, SMT		REV:	C
PART NO.	MD2-60ST-SMT		UNITS:	MM [INCHES]
DRAWN BY:	ZRJ	APPROVED BY:	SCALE:	
			3:1	

PC FILE NAME:
MD2-60ST-SMT

COPYRIGHT 2007 BY CUI INC.