


### **Features and Benefits**

- Very high photo sensitivity
- Supply voltage range 4.1V to 5.5V
- Standard SO8 package with open cavity
- Standard DFN3x3 with open cavity
- TTL and CMOS compatible
- Open drain output
- Active low output signal
- Lead free component, suitable for lead free soldering profile 260°C (target), MSL3
- Ideal for automotive applications

### **Ordering Information**

<b>Part No.</b>	<b>Temperature Code</b>	<b>Package Code</b>	<b>Option Code</b>	<b>Delivery Form</b>
MLX75303	E -40°C to 85 °C	XD SO8 Open Cavity		Tape On Reel
MLX75303	E -40°C to 85 °C	XE DFN3x3 Open Cavity		Tape On Reel

## 1 Functional Diagram



## 2 General Description

The MLX75303 is a CMOS integrated optical Schmitt trigger sensor with an integrated photodiode. The sensor is intended for automotive applications wherein infrared LEDs are used.

The MLX75303 block diagram is shown in Section 1 and contains following blocks: a trans impedance amplifier to convert and amplify the photocurrent of the photodiode, a voltage reference, a Schmitt trigger and an open drain output stage.

## **Table of Contents**

<b>1</b>	<b>Functional Diagram.....</b>	<b>2</b>
<b>2</b>	<b>General Description.....</b>	<b>2</b>
<b>3</b>	<b>Pin Definitions and Descriptions .....</b>	<b>4</b>
<b>4</b>	<b>Absolute Maximum Ratings .....</b>	<b>4</b>
<b>5</b>	<b>MLX75303 Specifications .....</b>	<b>5</b>
<b>6</b>	<b>Timing diagrams .....</b>	<b>6</b>
<b>7</b>	<b>Test diagrams.....</b>	<b>7</b>
<b>8</b>	<b>Applications Information.....</b>	<b>8</b>
<b>9</b>	<b>SO8 Open Cavity Package Information.....</b>	<b>9</b>
<b>10</b>	<b>DFN3x3 Open Cavity Package Information.....</b>	<b>10</b>
<b>11</b>	<b>Standard information regarding manufacturability of Melexis products with different soldering processes.....</b>	<b>11</b>
<b>12</b>	<b>ESD Precautions .....</b>	<b>11</b>
<b>13</b>	<b>Disclaimer.....</b>	<b>12</b>

### 3 Pin Definitions and Descriptions

Pin Number	Pin Name	Description	Type
1	Vss	Ground connection	Ground
2	OUT	Active low (= light on) output	Open drain output
3	Vdd	Power supply	Supply
4	N.C.	Not connected	Floating
5	N.C.	Not connected	Floating
6	N.C.	Not connected	Floating
7	N.C.	Not connected	Floating
8	N.C.	Not connected	Floating

### 4 Absolute Maximum Ratings

Valid for all MLX75303 versions. All voltages are referenced to Vss.

Symbol	Rating	Value	Unit
Vdd	Supply Voltage, $V_{DD}$ (over voltage)	-0.3 to 7	V
$V_{out}$	DC Output Voltage	-0.3 to $V_{dd}+0.3V$	V
$I_{out}$	DC Output Current, per Pin	$\pm 20$	mA
$T_{Stg}$	Storage Temperature Range, $T_s$	-40 to 125	°C
$V_{ESD-HBM}$	ESD Sensitivity (Human Body Model according to CDF-AEC-Q100)	4	kV
$V_{ESD-MM}$	ESD Sensitivity (Machine Model according to CDF-AEC-Q100)	200	V

For proper operation  $V_{out}$  should be constrained to the range  $V_{ss} \leq V_{out} \leq V_{dd}$ .

Exceeding the absolute maximum ratings may cause permanent damage. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

## 5 MLX75303 Specifications

All voltages are referenced to Vss.

Symbol	Parameter	Conditions	Min	Typ	Max	Units	Test <sup>1</sup>
Vdd	Supply Voltage		4.1		5.5	V	V
Idd	Static Power Supply Current	At Vdd=5.5V, unloaded output			2	mA	V
E <sub>eon</sub>	Irradiance for Threshold "on"	Vdd=5V, $\lambda=880\text{nm}$ , $T_{\text{amb}}=25^\circ\text{C}$	70		140	$\mu\text{W}/\text{cm}^2$	V
E <sub>eoff</sub> /E <sub>eon</sub>	Hysteresis	Vdd=5V, $\lambda=880\text{nm}$	60		80	%	V
TC	Temperature Coefficient of threshold "on"	Vdd=5V, $\lambda=880\text{nm}$		-0.44		%/K	X
E <sub>emax</sub>	Absolute Maximum Irradiance	Vdd=5V, $\lambda=880\text{nm}$ , $T_{\text{amb}}=25^\circ\text{C}$			15 x E <sub>eon_max</sub>	$\mu\text{W}/\text{cm}^2$	X
$\lambda_{0.3}$	Spectral Bandwidth	$T_{\text{amb}}=25^\circ\text{C}$	500		1000	nm	X
V <sub>OL</sub>	Output voltage low	Vdd=5.5V, E <sub>e</sub> >E <sub>on</sub> , I <sub>OL</sub> =16mA	0		0.4	V	V
V <sub>OH</sub>	Output voltage high	Vdd=5.5V, E <sub>e</sub> =0			Vdd+0.3	V	X
I <sub>OH</sub>	High level output current	Vdd=5.5V, E <sub>e</sub> =0	0		1	$\mu\text{A}$	V
t <sub>Vdd_rise</sub>	Vdd rise time	10..90% of Vdd		4		$\mu\text{s}$	V
t <sub>setup</sub>	Electrical setup-time	R <sub>L</sub> =1kOhm, C <sub>L</sub> =2nF, $\lambda=880\text{nm}$	0		24	$\mu\text{s}$	V
S <sub>pd</sub>	Area of photodiode			0.36		$\text{mm}^2$	D
t <sub>f</sub>	Fall time	(a), E <sub>e</sub> =E <sub>eon_max</sub>	0		300	ns	X
t <sub>on</sub>	Turn-on time	(a), E <sub>e</sub> =E <sub>eon_max</sub>	0	10	20	$\mu\text{s}$	V
t <sub>off</sub>	Turn-off time	(a), E <sub>e</sub> =15xE <sub>eon_max</sub>	0	10	20	$\mu\text{s}$	V
t <sub>p</sub>	Light pulse duration	(a)	20			$\mu\text{s}$	V
t <sub>G</sub>	Light pulse rejection	(a)		2		$\mu\text{s}$	X
T <sub>A</sub>	Operating Temperature Range		-40		85	°C	V

(a) Vdd=5V, R<sub>L</sub>=1kOhm, C<sub>L</sub>=2nF,  $\lambda=880\text{nm}$  (LED type SFH421)


<sup>1</sup> The column *Test* indicates if the specific parameter is tested in production. Following symbols are used:

V: the specific parameter is tested in production


X: the specific parameter is verified in characterisation, but is not tested in production (e.g. timings and capacitances)

D: the specific parameter is guaranteed by design and is not tested as such in production


## 6 Timing diagrams




Definition of the switch-on and switch-off thresholds



Definition of the switch-on and switch-off delays




Definition of the power-on delay




Definition of the light pulse duration

## 7 Test diagrams

Measurement and trimming of  $E_{eon}$ ,  $E_{eoff}$  and hysteresis:




Functional check of  $E_{eon}$  and  $E_{eoff}$  thresholds and timing measurements (Go-NoGo tests):



## 8 Applications Information

A typical connection diagram is shown in the figure below. A load resistor  $R_L$  is needed to get a voltage level out. The load capacitance  $C_L$  is typically formed by the input capacitance of the component that is connected to the sensor output, the wiring capacitance and the output capacitance of the sensor itself.




Decoupling capacitors between  $Vdd$  and  $Vss$  (1uF in parallel with 100nF) are highly recommended in all configurations.

Recommendation: every change in the application should be agreed by both parties.


## 9 SO8 Open Cavity Package Information

SO8 open cavity package, MSL3, 260°C soldering profile (target). Lead free component.



### 10 DFN3x3 Open Cavity Package Information

DFN3x3 open cavity package, MSL3, 260°C soldering profile (target).



## **11 Standard information regarding manufacturability of Melexis products with different soldering processes**

Our products are classified and qualified regarding soldering technology, solderability and moisture sensitivity level according to following test methods:

### **Reflow Soldering SMD's (Surface Mount Devices)**

- IPC/JEDEC J-STD-020  
Moisture/Reflow Sensitivity Classification for Nonhermetic Solid State Surface Mount Devices  
(classification reflow profiles according to table 5-2)
- EIA/JEDEC JESD22-A113  
Preconditioning of Nonhermetic Surface Mount Devices Prior to Reliability Testing  
(reflow profiles according to table 2)

### **Wave Soldering SMD's (Surface Mount Devices)**

- EN60749-20  
Resistance of plastic- encapsulated SMD's to combined effect of moisture and soldering heat

### **Solderability SMD's (Surface Mount Devices)**

- EIA/JEDEC JESD22-B102 and EN60749-21  
Solderability

For all soldering technologies deviating from above mentioned standard conditions (regarding peak temperature, temperature gradient, temperature profile etc) additional classification and qualification tests have to be agreed upon with Melexis.

The application of Wave Soldering for SMD's is allowed only after consulting Melexis regarding assurance of adhesive strength between device and board.

Melexis is contributing to global environmental conservation by promoting **lead free** solutions. For more information on qualifications of **RoHS** compliant products (RoHS = European directive on the Restriction Of the use of certain Hazardous Substances) please visit the quality page on our website: <http://www.melexis.com/quality.asp>

## **12 ESD Precautions**

Electronic semiconductor products are sensitive to Electro Static Discharge (ESD).  
Always observe Electro Static Discharge control procedures whenever handling semiconductor products.

## **13 Disclaimer**

Devices sold by Melexis are covered by the warranty and patent indemnification provisions appearing in its Term of Sale. Melexis makes no warranty, express, statutory, implied, or by description regarding the information set forth herein or regarding the freedom of the described devices from patent infringement. Melexis reserves the right to change specifications and prices at any time and without notice. Therefore, prior to designing this product into a system, it is necessary to check with Melexis for current information. This product is intended for use in normal commercial applications. Applications requiring extended temperature range, unusual environmental requirements, or high reliability applications, such as military, medical life-support or life-sustaining equipment are specifically not recommended without additional processing by Melexis for each application.

The information furnished by Melexis is believed to be correct and accurate. However, Melexis shall not be liable to recipient or any third party for any damages, including but not limited to personal injury, property damage, loss of profits, loss of use, interrupt of business or indirect, special incidental or consequential damages, of any kind, in connection with or arising out of the furnishing, performance or use of the technical data herein. No obligation or liability to recipient or any third party shall arise or flow out of Melexis' rendering of technical or other services.

© 2005 Melexis NV. All rights reserved.

For additional information contact Melexis Direct:

Europe, Africa, Asia: Phone: +32 1367 0495 E-mail: sales\_europe@melexis.com America: Phone: +1 603 223 2362 E-mail: sales\_usa@melexis.com

ISO/TS 16949 and ISO14001 Certified