


Part Number: MS22 12102

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Use -B after Ametherm's part #

For example: to order an inside kinked lead use part number MS22 12102-A



Electrical Specifications:

Resistance @ 25°C	120.0 $\Omega \pm 25\%$
Max Steady State Current Up to 65°C	2.0 A
Max Recommended Energy Rating (Joules)	220.0 J
Actual Failure Point of Instantaneous Energy (Joules)	450.0 J
Resistance @ 100% of Max Current	1.780 Ω
Resistance @ 50% of Max Current	3.650 Ω
Body Temperature @ 100% Current Rating	155 °C
Dissipation Constant	75.4mW/°C
Thermal Time Constant	124 seconds
Material Type	"M"
Max Recommended Capacitance @120VAC/240VAC/440VAC/700VAC	15000 μ F 3800 μ F 1100 μ F/450 μ F

Mechanical Specifications:

D	20.0 ± 1.0 mm
T	7.0 ± 0.7 mm
Lead Diameter	1.0 ± 0.1 mm
S	7.8 ± 2.0 mm
L	38.0 ± 9.0 mm
Straight Leads Coating Run Down	5.0 ± 1.0 mm
B	9.3 ± 0.85 mm
C	3.82 ± 1.0 mm

Revision Date: March 19, 2003

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
 Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670

www.ametherm.com