



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: N520-01M

Multimode Fiber Optics 1-meter (3-ft.) Duplex MMF 50/125 Patch Cable, LC/LC

Highlights



- Premium PVC multimode patch cables
- Attenuation loss meets or exceeds the latest industry standards
- Loop-back cables provide an easier, "single-person" solution for testing fiber optic cable systems
- Higher bandwidth optimized for gigabit and 10Gbps networks
- Backward compatible with 62.5 micron fiber
- Built-in headroom for future applications

Description

Tripp Lite's 1-meter multimode duplex Fibre Channel optic LC/LC patch cable is manufactured from 50/125 zipcord fiber. The cable has LC connectors on each end. It has a PVC jacket and is FDDI and OFNR rated. 50/125 Duplex multimode fiber is most commonly used in Fibre Channel applications. It is backward compatible with 62.5 micron fiber and provides built-in headroom for future applications. The cable provides higher bandwidth optimized for Gigabit and 10Gbps networks as well. Also available in lengths up to 152 meters. Enter "N520-" in the search field to bring up all lengths. For LC-SC cables, search "N516-", and for SC-SC, search "N506-". Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

Any fiber optic hardware or NIC card requiring multimode duplex cable with LC/LC connectors

Package Includes

1M duplex MMF cable LC/LC 50/125 fiber

Features

- Constructed with 50/125 micron cable
- Length: 1-meter
- Use on fiber and fibre channel installations
- LC male to LC male connectors
- Higher bandwidth optimized for gigabit and 10Gbps networks
- Backward compatible with 62.5 micron fiber
- Built-in headroom for future applications
- Number of fibers: 2
- Fiber type: All glass graded index
- Core diameter: Two 50+/-3 microns
- CLAD diameter: 125+/-2 microns
- Primary coating diameter: 245+/-15 microns
- Primary coating material: Acrylate
- Secondary coating diameter: 900+/-50 microns
- Secondary coating material: PVC
- Attenuation @850NM: 3.5DB/KM maximum, @1300NM: 1.0DB/KM maximum

Bandwidth @850NM: 220 MHz-KM minimum, @1300NM: 600 MHz-KM minimum
 Numerical aperture: .275 nominal
 Proof test level: 100,000 PSI
 Insertion loss testing performed on every connector (0.2db typical) and provided with cable
 Beveled edge on ends of glass makes insertion of plug a breeze
 Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW	
Attenuation @ 850NM	3.5DB/KM maximum, @1300NM: 1.0DB/KM maximum
Bandwidth @ 850NM	220 MHz-KM minimum, @1300NM: 600 MHz-KM minimum
Clad Diameter	125+/-2 microns
Core Diameter	Two 50+/-3 microns
Fiber Type	All glass graded index
Number of Fibers	2
Numerical Aperture	.275 nominal
Primary Coating Diameter	245+/-15 microns
Primary Coating Material	Acrylate
Proof Test Level	100,000 PSI
Secondary Coating Diameter	900+/-50 microns
Secondary Coating Material	PVC
PHYSICAL	
Color	Orange
Style	Fiber Optic
Length	1 m
CONNECTIONS	
Connector A	 LC
Connector B	 LC
Connector C	 LC
Connector D	 LC
Number of Connectors	4
CERTIFICATIONS	
Certifications	ROHS

Related Items

Fiber Optic Cables & Adapters		
N520-03M	Multimode Fiber Optics 3-meter (10-ft.) Duplex MMF 50/125 Patch Cable, LC/LC	Qty: [optional]
N520-10M	Multimode Fiber Optics 10-meter (33-ft.) Duplex MMF 50/125 Patch Cable, LC/LC	Qty: [optional]

N520-50M	Multimode Fiber Optics 50-meter (165-ft.) Duplex MMF 50/125 Patch Cable, LC/LC	Qty: [optional]
N520-30M	Multimode Fiber Optics 30-meter (100-ft.) Duplex MMF 50/125 Patch Cable, LC/LC	Qty: [optional]
N520-15M	Multimode Fiber Optics 15-meter (50-ft.) Duplex MMF 50/125 Patch Cable, LC/LC	Qty: [optional]
N520-05M	Multimode Fiber Optics 5-meter (16-ft.) Duplex MMF 50/125 Patch Cable, LC/LC	Qty: [optional]
N520-02M	Multimode Fiber Optics 2-meter (6-ft.) Duplex MMF 50/125 Patch Cable, LC/LC	Qty: [optional]
N516-01M	Multimode Fiber Optics 1-meter (3-ft.) Duplex MMF 50/125 Patch Cable, LC/SC	Qty: [optional]
N506-01M	Multimode Fiber Optics 1-meter (3-ft.) Duplex MMF 50/125 Patch Cable, SC/SC	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/EN/products/model.cfm?txtModelID=2611.