



	PAA191	Units
Blocking Voltage	400	V
Load Current	250	mA
Max R _{ON}	8	Ω

Features

- 5000V_{RMS} Input/Output Isolation
- Small 8 Pin DIP Package
- Low Drive Power Requirements (TTL/CMOS Compatible)
- No Moving Parts
- High Reliability
- Arc-Free With No Snubbing Circuits
- No EMI/RFI Generation
- Machine Insertable, Wave Solderable
- Surface Mount and Tape & Reel Versions Available

Applications

- Telecommunications
 - Telecom Switching
 - Tip/Ring Circuits
 - Modem Switching (Laptop, Notebook, Pocket Size)
 - Hookswitch
 - Dial Pulsing
 - Ground Start
 - Ringing Injection
- Instrumentation
 - Multiplexers
 - Data Acquisition
 - Electronic Switching
 - I/O Subsystems
 - Meters (Watt-Hour, Water, Gas)
- Medical Equipment-Patient/Equipment Isolation
- Security
- Aerospace
- Industrial Controls

Description

PAA191 is a dual 400V, 250mA, 8Ω 1-Form-A solid state relay. This performance leader provides a high blocking voltage capability and features an enhanced 5000V isolation barrier between the input and output circuits of the relay.

Approvals

These products comply with the requirements of:

- UL recognized: File #E76270
- CSA certified: File #LR43639
- Complies with:
 - EN 60950
 - IEC 950
 - AS/NZS 3260
 - EN 41003


Ordering Information

Part #	Description
PAA191	8 Pin DIP (50/Tube)
PAA191S	8 Pin Surface Mount (50/Tube)
PAA191STR	8 Pin Surface Mount (1000/Reel)


Pin Configuration

PAA191 Pinout

AC/DC Configuration



Switching Characteristics of Normally Open (Form A) Devices



Absolute Maximum Ratings (@ 25° C)

Parameter	Min	Typ	Max	Units
Input Power Dissipation	-	-	150 ¹	mW
Input Control Current	-	-	50	mA
Peak (10ms)	-	-	1	A
Reverse Input Voltage	-	-	5	V
Blocking Voltage	-	-	400	V
Total Power Dissipation	-	-	800 ²	mW
Isolation Voltage Input to Output (60 seconds)	-	-	5000	V _{RMS}
Operational Temperature	-40	-	+85	°C
Storage Temperature	-40	-	+125	°C
Soldering Temperature	-	-	+260	°C

¹ Derate Linearly 1.33 mW/°C

² Derate Linearly 6.67 mW/°C

Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at conditions beyond those indicated in the operational sections of this data sheet is not implied.


Electrical Characteristics

Parameter	Conditions	Symbol	Min	Typ	Max	Units
Output Characteristics @ 25°C						
Load Current* (Continuous) AC/DC Configuration	-	I _L	-	-	250	mA
Peak Load Current	10ms	I _{LPK}	-	-	500	mA
On-Resistance AC/DC Configuration	I _L =250mA	R _{ON}	-	6	8	Ω
Off-State Leakage Current	V _L =400V	I _{LEAK}	-	-	1	μA
Switching Speeds						
Turn-On	I _F =5mA, V _L =10V	T _{ON}	-	-	3.0	ms
Turn-Off	I _F =5mA, V _L =10V	T _{OFF}	-	-	1.0	ms
Output Capacitance	50V; f=1MHz	C _{OUT}	-	25	-	pF
Input Characteristics @ 25°C						
Input Control Current	I _L = 250mA	I _F	5	-	50	mA
Input Dropout Current	-	I _F	0.2	0.7	-	mA
Input Voltage Drop	I _F = 5mA	V _F	0.9	1.2	1.4	V
Reverse Input Voltage	-	V _R	-	-	5	V
Reverse Input Current	V _R =5V	I _R	-	-	10	μA
Input to Output Capacitance	-	C _{I/O}	-	3	-	pF


*NOTE: If both poles operate simultaneously load current must be derated so as not to exceed the package power dissipation value.

PERFORMANCE DATA*


PAA191
Typical LED Forward Voltage Drop
(N=50 Ambient Temperature = 25°C; $I_F = 5\text{mADC}$)




PAA191
Typical On-Resistance Distribution
(N=50 Ambient Temperature = 25°C)
(Load Current = 250mADC, $I_F = 5\text{mADC}$)




PAA191
Typical Blocking Voltage Distribution
(N=50 Ambient Temperature = 25°C)




PAA191
Typical I_F for Switch Operation
(N=50 Ambient Temperature = 25°C)
(Load Current = 250mADC)




PAA191
Typical I_F for Switch Dropout
(N=50 Ambient Temperature = 25°C)
(Load Current = 250mADC)




PAA191
Typical Turn-On Time
(N=50 Ambient Temperature = 25°C)
(Load Current = 250mADC; $I_F = 5\text{mADC}$)




PAA191
Typical Turn-Off Time
(N=50 Ambient Temperature = 25°C)
(Load Current = 250mADC; $I_F = 5\text{mADC}$)




PAA191
Typical Load Current vs. Temperature




PAA191
Typical Leakage vs. Temperature
(Measured across Pins 5 & 6 or 7 & 8)




PAA191
Typical Blocking Voltage vs. Temperature



PAA191
Typical Turn-On vs. Temperature
(Load Current = 250mADC)











PAA191
Typical Turn-Off vs. Temperature
(Load Current = 250mADC)



*The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.


PERFORMANCE DATA*




*The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.

MECHANICAL DIMENSIONS


8 Pin DIP Through Hole (Standard)




PC Board Pattern (Top View)



8 Pin DIP Surface Mount ("S" Suffix)




PC Board Pattern (Top View)



Dimensions
mm
(inches)

MECHANICAL DIMENSIONS

Tape and Reel Packaging for 8 Pin Surface Mount Package



NOTE: Tape dimensions not shown, comply with JEDEC Standard EIA-481-2

Dimensions
mm
(inches)

For additional information please visit our website at: www.clare.com

Clare, Inc. makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in Clare's Standard Terms and Conditions of Sale, Clare, Inc. assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

The products described in this document are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or where malfunction of Clare's product may result in direct physical harm, injury, or death to a person or severe property or environmental damage. Clare, Inc. reserves the right to discontinue or make changes to its products at any time without notice.